

5300 Series Printer



PACKED WITH FEATURES

- USB 2.0 and RS232 serial interfaces standard on every printer.
- Easily configured to work with most teller software solutions.
- Independent form validation of up to 14 printed lines.
- Semi-automatic self-loading feed mechanism simplifies paper loading and minimizes paper jamming.
- Snap-in ink jet cartridges ensure fast trouble-free replenishment.
- Configurable form guide.
- LED's indicate modes of operation, paper present, ink conditions and printer status.
- Small Footprint.

 Pertech

 UniLink™



SPECIFICATIONS

<u>Compatibility Modes Drivers</u>	Seven - Emulates most teller receipt printers Compatible with Windows 7, & 10
<u>Interface RS232</u>	DB9M Connector Baud Rates 9600, 19200 & 57600
<u>USB</u>	2.0 Compatible
<u>WiFi</u>	
<u>RF Certification</u>	FCC/CE-RED/IC/TELEC/KCC/SRRC/NCC
<u>Wi-Fi Certification</u>	Wi-Fi Alliance
<u>Wi-Fi Protocols</u>	802.11 b/g/n (802.11n up to 150 Mbps) A-MPDU A-MSDU aggregation and 0.4 µs guard interval support
<u>Frequency Range</u>	2.4 GHz ~ 2.5 GHz
<u>Supported Network Protocols</u>	TCP/IP: IPv4; IP Direct Mode; LPD; BOOTP/DHCP/ AutoIP; HTTP/HTTPS
<u>Under Development</u>	IOS Interface, Wi-Fi Direct Pertech Smart App (Android)
<u>Cash Drawer</u>	Optional on Model 5355
<u>Utilities</u>	Logo - Download - Configuration
<u>Power Supply</u>	15 Watt 24V Wall Mount
<u>Roll Paper</u>	Width 3.0" +/- .03" / (76mm +/- .762 mm) Diameter 3.5" Max./ (88.9 mm) Core ID 5/8" Min. / (15.875 mm) Original + 2, 5.5" by 2.75" Min.(139.7 x 69.9mm) .0015 to .0047
<u>Form</u>	Original + 2, 5.5" by 2.75" Min.(139.7 x 69.9mm)
<u>Thickness</u>	.0015 to .0047
<u>Total Media Thickness</u>	.012" Total (Includes Receipt) / (.305 mm)
<u>Print Speed</u>	Ink Jet: 5.0 LPS (Lines Per Sec.)@ 40 CPL(Character Per Line), 16 CPI (Character Per Inch) and 6 LPI (Lines Per Inch)
<u>Paper Feed</u>	5 Inches Per Second
<u>Printhead</u>	HP Inkjet C6602
<u>InkJet Cartridge</u>	Part # 108541001 (Black Ink)
<u>Line Pitch</u>	5, 6, 7, 8, LPI
<u>Character Sets</u>	USA
<u>Code Pages</u>	437 USA, 863 Canadian-French and 1252 Latin I
<u>Fonts</u>	Multiple Fonts Available
<u>Graphics</u>	InkJet: 12 Nozzle
<u>Print Line</u>	InkJet: 3" 96x160 DPI Standard Mode. 96x80 DPI Draft Mode.
<u>Validation</u>	Up to 14 Lines on Inserted Form at 8 LPI
<u>Noise</u>	62 db
<u>Expected Life</u>	
<u>Printhead</u>	100M Dots Per Cartridge
<u>PCB</u>	Over 61K hrs
<u>Mechanism</u>	15 Million Printed Lines
<u>Agency Listings</u>	FCC Class B, C CSA US, RoHS
<u>Dimensions</u>	Height 5.4" / (137 mm) Width 6.9" / (175 mm) Length 8.9" / (226 mm)
<u>Weight</u>	R/V Models 5.75 Lbs. / (2.61 kg) Ext. Power Supply 1.12 Lbs. Max. / (.051 kg)

APPROVED SOFTWARE *

Harland Oncore
EF4270/A470 Approved
Harland Oncore EZ Teller II
EF4270/A470 Approved
Fiserv Clear Touch Approved
Argo
ACL Approved
Compuflex
ACL Approved
System Innovators
ACL Approved
GCE Soft
ACL Approved
David Meyer Test Vendor
ACL Approved
Jack Henry
Vertex ACL or Mode3

* The 5300 family of printers can emulate other printer models.



 Pertech

 UniLink

Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980

Copyright© 2020 Pertech.
All Rights Reserved. Printed in U.S.A.
Product specifications are subject to change.