

ST9730

- Robust work group printer
- Performance & security



Model No.		ST9730		
Print Speed (pages/min.)		Up to 55 ppm		
Time to First Page		As fast as 4.8 seconds		
Maximum Duty Cycle (pgs./mo.)		Up to 250,000		
Recommended Volume (pgs./mo.)		3,000 - 20,000		
Maximum Resolution		1,200 x 1,200 dpi		
Processor		Dual Core, 800 MHz		
Memory (Standard/Max)		512MB / 2.5GB		
Standard Connectivity		USB 2.0 (Type B), 10/100/1000 Ethernet		
Optional Connectivity		Wireless Parallel Serial		
USB A Port		Front		
Duplex Printing		Optional		
Paper Capacity*	Standard (in/out) Maximum (in/out)	650/550 4,400/2,550		
Paper Sources	Standard (in/out) Maximum (in/out)	2/1 6/3		
Emulations		PS3, PCL 5e, PCL6, PPDS, PDF 1.7, HTML, Microsoft XPS, Direct Image		
Operator's Panel		2.4" Color Display and Numeric Pad		
MICR Cartridge Yields*		Starter: 8k, Replacement: 8k, 17k		
Imaging Unit**		Up to 70,000		
Dimensions		16.7 x 20.1 x 16.3		
Weight (lbs.)		52.2		
Warranty		1-year, return-to-depot from date of sale		
Quality Assurance Features		Auto Density Control MICR Toner Detection Originally Manufactured MICR Toner Regulated Fuser Temperature	Low Toner Warning and Auto Stop Optimized Fusing & Transfer Voltage 3 Year MICR Guarantee to ANSI/ABA Stan- dards	
Secure Fonts		E-13B MICR Font CMC7 MICR Font Microprint Font	Secure Numeric Font ICR Numeric Font	
Security Features		Front Panel Security Lock Set Copies to one (1) Auto Jam Recovery Disable Password Protection DES Encryption/Decryption	Audit Trail Tray Locking MICRpoint Datastream Tray Protection Optional: Physical Drawer Locks	
Options		250 Sheet Tray, 550 Sheet Tray 2100 Sheet Tray (Not for MICR Printing) Staple Finisher Output Expander	4-Bin Mailbox High Capacity Output Expander Caster Base Swivel Cabinet	

^{*20}lb or 75 GSM Paper. Maximum input amount shown is the maximum capacity that can be used for non-MICR printing: high-capacity input trays may interfere with printing quality MICR documents. The maximum input capacity for MICR printing may be lower than the values shown.

1Average standard page yield value declared in accordance with ISO/IEC 19752.

SECURE MICR PRINTERS

²Maximum Yield estimate based on 3 average letter/A4-size pages per print job at approximately 5% coverage. Actual yield may vary. All specifications are subject to change without notice.



Secure MICR Printers-ST 9730

MICR Feature	Description	Benefit
E13B Font	Widely accepted MICR font used in printing MICR encoded documents in the US, Canada, Mexico, the Far-East and some other countries	Meets ASC X9B/US specification for MICR font and necessary to process checks through the system
CMC7 Font	Alternative MICR font used to print MICR encoded documents in many European and most Latin American countries. Numeric character set only	Meets international standards (ISO) 1004.
Secure Numeric Font	Unique ST-designed font that is very difficult to alter because of a special background and very small text & numeric print embedded in the amount line of the check.	Additional layer of security at the document level. Minimizes the risk of fraud.
Microprint Font	Extremely small type font allows one to embed micro text and numbers inside lines of print on the MICR document. Denoted by the letters "MP."	Additional layer of security at the document level. Minimizes the risk of fraud.
ICR Numeric Font	Image readable secure font designed to be read by imaging equipment utilized by many financial institutions.	Additional layer of security at the document level. Minimizes the risk of fraud.
Front Panel Security Lock	Additional security beyond password protection. User must enter an 8 digit combination prior to printing.	Additional layer of security at the document level. Minimizes the risk of fraud.
Set Copies to one (1)	A PCL setting that tells the printer to print the job only once.	Prevents fraud by disallowing the printing of multiple copies of a document.
Auto Jam Recovery Disable	Automatically turns Jam Recovery OFF when checks are being printed	Prevents multiple copies of a check from being printed
Password Protection	Prevents access to check-printing resources (stored signatures, MICR fonts, form overlays) without the proper password	Prevents unauthorized access to MICR and Secure fonts, and user-specific signatures and form overlays
MICR Toner Detection	Detects whether MICR toner or regular toner is installed in the printer	Prevents printing of MICR documents with regular ton- er- preventing costly bank rejects
Toner Low Warnings	Printer alerts user when MICR toner is low	Ensures quality MICR printing
DES Encryption/Decryption	Decrypts the print data stream, protecting it while it is being transmitted to the printer	One of the highest levels of security available- the printer decrypts the code prior to printing
Audit Trail	Creates user-defined reports of check printing activity for auditing purposes	Gives user a written record of check printing activity
3 Year MICR Guarantee to ANSI/ABA Standards	Source Technologies ensures the readability performance of our MICR printers	Ensures the quality of printed negotiable documents
Auto Density Control for Toner	Ensures conformance to signal strength standards throughout cartridge life	Ensures conformance and bank acceptance
Originally Manufactured MICR Toner Cartridge	Toner cartridges are built and tested using MICR toner	No "refilled" or "remanufactured" cartridges to introduce potential problems that would damage the printer
Regulated Fuser Temperature for Optimum Performance	Fusing temperature controlled to match MICR toner and check stock paper weights	Maximizes toner adherence. Less exposure to fraud due to less toner lift off
Tray Locking	Key lock on printer and expansion drawers	Prevents fraud by keeping check stock safe and prevents check paper waste
MICRpoint	Allows fine tuning of the position of the MICR line	Accounts for minor variations between printers. Prevents bank rejection of checks.
Datastream Tray Protection	Limits the ability of non-MICR jobs to print from specified trays.	Keeps regular office documents from being printed on check stock. Reduces the amount of re-printed be- cause of printing to the wrong tray and reduces the cost of replacing misused check stock.

For more information or to order, please contact:

