



To order or for more information:

Tel: 1-800-666-2980

E-mail: [info@unilinkinc.com](mailto:info@unilinkinc.com)

Web: [www.unilinkinc.com](http://www.unilinkinc.com)

## UNISYS e-@ction SLIP/VALIDATION/ RECEIPT PRINTER

UNISYS



The Unisys e-@ction Slip, Validation, and Receipt Printer (EFP 9800) Series is designed for maximum flexibility and performance at the lowest possible cost.

### **Benefits and Capabilities**

- ▶ Small footprint
- ▶ High performance printing
- ▶ Receipt with journal reel
- ▶ Document validation
- ▶ Check/slip printing
- ▶ Optional MICR reader
- ▶ Serial or parallel port models
- ▶ Flash memory
- ▶ Resident emulations

The Slip, Validation, and Receipt printers are highly functional additions to the Unisys family of payment peripherals. They are designed to print high speed receipts, slips, checks, other documents and validate documents while recording transactions.

The Slip, Validation, and Receipt printers are part of the overall Unisys solution for financial institutions and other organizations requiring high quality, specialized printing.

### **Simply Reliable**

No preventative maintenance is required for the EFP 9800 Series during regular work cycles. Its simple design minimizes moving parts, providing unmatched reliability and reduced service costs.

For more information, contact



To order or for more information:

Tel: 1-800-666-2980

E-mail: [info@unilinkinc.com](mailto:info@unilinkinc.com)

Web: [www.unilinkinc.com](http://www.unilinkinc.com)

**Premier Technology**

The EFP 9800 Series ability to read MICR and print the check and journal in one small footprint make this printer truly unique. A world of possibilities open to a market that previously could not afford the stand-alone MICR reader option. With the EFP 9800 standard MICR reader a whole new standard is being set for station printers.

**Slip/Validation/Receipt Printer Technical Product Specifications**

Print Technology	Bi-directional, logic seeking, 9-pin impact print technology	
Print Speed	290 lines per minute (up to 4.8LPS and up to 260 CPS) at 40 columns print speed	
Print Columns	From 24 to 66 columns (42 columns standard)(emulation dependent)	
Print Density	Variable horizontal density from 10 to 23 cpi(emulation dependent)	
Standard Features	Flash memory 4 KB buffer Journal/rewind Cover open switch Paper and document sensors Easily installed 1 or 2 ply paper roll with "clamshell" design Snap-in high-quality re-inking ribbon cartridge (black or purple: 5 M characters average) External, autoranging power supply LED status indicators and power switch	
Emulations Resident	Epson ESC/POS, NCR 5021 (serial only), IPI Pro Printer, DH 4700 and extended Unisys EF 4270 emulations	
Validation	Up to 16 lines of validation (emulation dependent)	
Character Sets Resident	Multinational character sets: U.S., U.K., French, Italian, German, Spanish, Danish I/II, Swedish, Norwegian, Hebrew and Japanese (emulation dependent)	
Bar Codes Supported	UPC-A, UPC-E, code 39, code 128, EAN\JAN 8 and EAN\Jan 13, interleaved 2 of 5 and codabar	
Forms	Ability to handle 3 part forms plus receipt and journal	
Options	E-13B/CMC-7 switch selectable MICR reader Serial (EFP 984x) or IEEE 1284 parallel port (EFP 985x) (communications cables ordered separately)	
Dimensions	Width: 165 mm (6.5 in.) Depth: 254 mm (10.0 in.) Height: 165 mm (6.5 in.) Weight: 3.7 kg (7.5 lbs.)	
Power	Voltage: 100-240 VAC @ 50/60 Hz (line cords ordered separately)	
Noise Level	63 dbA	
Certifications	UL 1950, CSA, IEC 950 EN60950, EN55022 (CE class B) FCC Part 15 Class A	
Services	Warranty: 12 months Service: Unisys Global Network Services Maintenance: No preventive maintenance required	Specifications are subject to change without notice Unisys is a registered trademark and e-action is a trademark of Unisys Corporation. All other brand names and product names are acknowledged to be the service marks, trademarks or registered trademarks of their respective holders. © 2000 Unisys Corporation
Consumables	Contact UniLink at 1-800-666-2980	