



- USB or Ethernet Models Available
- Modular Design Saves Counter Space
- Remove/Replace Paper Rolls Without Disconnecting Scanner
- Economical and Easy Thermal Printing
- Print Graphics on Your Receipts
- Engineered for Durability

Prints receipts right at your check scanner. Engineered to fit under Digital Check SmartSource scanners – combining scanner and receipt printer units into one footprint, saving valuable counter space!

### SmartSource ReceiptNOW

Designed to fit under the SmartSource Professional, Value, Expert, Adaptive, and Digital Check TellerScan TS240 scanners.

### SmartSource ReceiptNOW Elite

Engineered to fit beneath the SmartSource Elite series scanners, and the Digital Check TellerScan TS500 scanners.

### SmartSource ReceiptNOW Ethernet Elite

Engineered to fit beneath the SmartSource Elite series scanners and network-enable your printer. This printer includes both an Ethernet and USB connection, and can operate in either environment.

### Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Largest paper roll
- Full or partial paper cut

### Compatibility

- USB or Ethernet interface
- Full 108 standard and international fonts with barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- Worldwide certifications

### Customizable Teller Receipts

- Top/bottom logos
- Border messages
- Watermarks
- Windows True Type fonts
- Color text/graphics – using 2-color paper

## PRODUCT SPECIFICATIONS

### Models

SRN2PTR-USB – ReceiptNOW with USB Interface  
SRN2PTR-ETH – ReceiptNOW with Ethernet Interface  
SRNELITE-USB – ReceiptNOW Elite with USB Interface  
SRNELITE-ETH2 – ReceiptNOW Elite with Ethernet Interface

### Printer Dimensions

#### ReceiptNOW

Height: 5.4 in (13.7 cm)  
Width: 6.1 in (15.5 cm)  
Length: 11.10 in (28.19 cm)

#### ReceiptNOW Elite

Height: 7.50 in (19.05 cm)  
Width: 5.10 in (12.95 cm)  
Length: 15.3 in (38.8 cm)

### Printing/Feed/Cut

Direct Thermal Printer  
Black and Two Color Capability (with 2-color paper)  
Black Print Speed 8 inches per second (20 cm per second)  
Resolution: 203 x 180 dpi  
95 Alphanumeric, 13 International Characters with Kanji  
True Type Fonts available when being driven as a  
Windows printer  
1D/2D Bar Code Fonts  
512K On-board Logo Flash  
Full/Partial Auto Cutter

### Controls

On/Off Switch  
Paper Empty/Low LED's with audible alerts  
Paper Feed Button  
Paper Width Adjustment  
Power Indicator

### Paper/Loading

Standard, Security, Non-BPA, 2-color Paper  
Paper Widths: 2.4 in to 3.25 in (6.1 cm to 8.3 cm)  
Paper Roll Diameter: 3.25 in (8.3 cm)  
Slide Out Tray, Drop-in Paper

### Interface

USB or Ethernet Models Available  
Standard ESC/POS Command Set  
OPOS & JavaPOS, Auto Status Back (ASB)

### ReceiptNow Elite SmartSource Elite TellerScan TS500



### ReceiptNow SmartSource Professional TellerScan TS240



### Included Accessories

USB 2.0 cable and international 100-240VAC, 50/60Hz  
power supply included

### Graphic Receipt Customization

Multiple Graphics Can be Placed Anywhere  
Custom Messages  
Watermarks

### Supported Operating Systems

Windows 8®, Windows 10® (32/64 bit versions)  
Mac OS and Linux  
(Contact Digital Check Technical Support for specific versions supported)

### Standard Warranty

3 year depot warranty

### Environmental

Operating Temperature: 41° - 104° F (5° - 40° C)  
Operating Humidity: 20 - 90% non-condensing

### Certifications

CE, UL, FCC Class B, ICES, VCCI



THE SECURE CHOICE™

