



SmartSource  
ReceiptNOW Elite



SmartSource  
ReceiptNOW

### Our Customers Say it Best!

“Integrating the ReceiptNOW printers and SmartSource scanners enabled us to deliver an enhanced client experience while capitalizing on processing efficiencies.” – Rachel Emery, AVP Office Automation Manager, United Bank & Trust

## SmartSource ReceiptNOW

Prints receipts right at your check scanner. Engineered to fit under Digital Check SmartSource scanners – combining scanner and receipt printer units into one footprint, saving valuable counter space!

**SmartSource ReceiptNOW** — Designed to fit under the SmartSource Professional, Value, Expert, Adaptive, and other scanners.

**SmartSource ReceiptNOW Elite** — Engineered to fit beneath the SmartSource Elite series scanners.

### Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Largest paper roll
- Full or partial paper cut

- Fast 8 inches/second (20 cm/second) delivery
- Less maintenance than matrix printers
- Fast installation for existing sites
- Three year warranty (advanced exchange available)

### Compatibility

- USB or Ethernet interface
- Full 108 std & international fonts w/barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- Worldwide certifications

### Customizable Teller Receipt

- Top/bottom logos
- Border messages
- Watermarks
- Windows True Type fonts
- Color text/graphics – using 2-color paper



## SmartSource ReceiptNOW Technical Information

### Models

SRNELITE-USB – ReceiptNOW Elite, USB Interface  
SRNELITE-ETH – ReceiptNOW Elite, Ethernet Interface  
SRN2PTR-USB – ReceiptNOW, USB Interface  
SRN2PTR-ETH – ReceiptNOW, Ethernet Interface

### Printing/Feed/Cut

Direct Thermal Printer  
Black and Two Color Capability  
Black Print Speed 8 inches/second (20 cm/second)  
Resolution: 203 x 180 dpi  
95 Alphanumeric, 13 International Characters w/Kanji  
True Type Fonts available when being driven as a Windows printer  
1D/2D Bar Code Fonts  
512K on-board Logo Flash  
Full/Partial Auto Cutter

### Controls

On/Off Switch  
Paper Empty/Low LED's w/Audible Alerts  
Paper Feed Button  
Paper Width Adjustment  
Power indicator

### Interface

USB  
Standard ESC/POS Command Set  
OPOS & JavaPOS, Auto Status Back (ASB)

### Dimensions

	ReceiptNOW	ReceiptNOW Elite
Height:	5.4 inches (13.7 cm)	5.2 inches (13.2 cm)
Width:	6.1 inches (15.5 cm)	5.7 inches (14.5 cm)
Length:	15.3 inches (38.8 cm)	9.5 inches (24.2 cm)

### Environment/Acoustics

5~50°C Operating Environment  
Acoustics < 60 dba Cutting or Printing



### Power

International Power 100-240VAC, 50/60Hz  
Power Supply Included

### Paper/Loading

Standard, Security, Non-BPA, 2-Color Paper  
2.4 in. to 3.25 in. (6.1 cm to 8.3 cm) Paper Widths - Adjustable  
Largest 3.25 in. (8.3 cm) Diameter Paper Roll  
Slide Out Tray, Drop-in Paper

### Warranty/Service

3 Year Warranty  
Advanced Exchange Available

### Graphic Receipt Customization

Multiple Graphics Can be Placed Anywhere  
Custom Messages  
Watermarks

### Host OS

Win 2000, XP, Vista (32/64), Windows 7 (32/64), Windows 8 (32/64),  
Windows 10 (32/64)

### Maintenance

Print Exerciser & Diagnostic Software  
Operator Guide

### Certifications

FCC Class B, CE, VCCI, for EMI Emissions  
CE, for Susceptibility and ESD  
CE, CB, CUL/UL 60950, for Safety  
RoHS Compliant (EU)  
2010 Appliance Efficiency Regulations, California, Title 20

NOTES: Not every API Operating System combination may be qualified. Contact your application provider for more information. Specific capabilities may not be supported by every API or will require a minimum API version. Contact Digital Check for more information.

For more information about the entire line of Digital Check remote capture products, call **800-666-2980**

or visit [www.UniLinkinc.com](http://www.UniLinkinc.com)

SmartSource and ReceiptNOW are registered trademarks of Digital Check Corp. Ranger is a registered trademark of Silver Bullet Technology, Inc. All other brands and products referenced in this document are acknowledged to be the trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.

**UniLink**™