

To order or for more information:

Tel: 1-800-666-2980
E-mail: info@unilinkinc.com
Web: www.unilinkinc.com

Unisys EF 4270 Validation and Receipt Printer Series





The Unisys Validation and Receipt Printers are designed in response to numerous requirements expressed by Unisys customers all over the world.

The Validation and Receipt Printer series is particularly outstanding in the following areas:

- Ease of operation
- Reliability
- Conservation of space
- High transaction throughput
- Ergonomic design

The Unisys Validation and Receipt Printers are compact, highly functional additions to the Unisys family of financial peripherals, expressly designed to validate checks, record transactions on hard copy journal and dispense excellent quality receipts.

The EF 4270 Validation and Receipt Printer Series is an integral part of the overall Unisys solution for worldwide financial institutions and public sector agencies or for any organization that requires a cost-effective, specialized form output device, capable of high quality printing.

Benefits and Capabilities

- ► High speeds up to 264 characters per second (cps)
- ► Multiple-part, multiple-size document handling
- ► Easily replaceable, cost-effective consumables and supplies
- ► Independent feeds for validation and receipt/journal operation
- ▶ 5 pitch and font combinations with variable intercharacter spacing
- ► Entry level model reduces cost without sacrificing performance



To order or for more information:

Tel: 1-800-666-2980 E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

The EF 4270 Printer Series Advantage

- ► Intelligent, microprocessor-based 9-wire dot matrix printers EF 4271 (without take-up reel) EF 4272 (with take-up reel) EF 4275 entry level (w/o take-up reel)
- ► Bi-directional print speed up to 4 lines per second (lps) and up to 264 cps
- ▶Up to 17 lines of validation
- ► Autographic window (EF 4272 only)
- ► Single RS-232C serial port
- ► Centronics parallel interface port (EF 4271/EF4272 only)
- ► Selectable baud rates up to 19200 (communications cables ordered separately)

- ► Easily installed 1-ply or 2-ply paper roll
- ➤ Snap-in, high-quality ribbon cartridge (black: 2 M characters, purple: 4 M characters)
- ► Multinational character sets including: U.S., U.K., French, Italian, German, Spanish/Latin American and Hebrew
- ► Variable vertical line spacing programmable in 1/48ths of an inch
- ► Variable horizontal density from 6 to 24 characters per inch (cpi)
- ▶ 16 to 66 characters per line
- ► Line graphics and graphics printing capability

- ► Ability to handle up to 4-part forms and rece
- ▶32 KB fl software
- ▶7 KB data input buffer
- ► EF 4260 downloadable emulation and character sets
- ► Low paper and document presence detectors (EF 4271/EF 4272 only)
- ▶ Local or remote control form handling
- ► External, autoranging power supply
- ► Easily accessible On/Off switch and LED displays

Specifications

Physical Characteristics

	EF 4271 / EF 4275	EF4272	Power Supply
Height:	5.6 in (141 mm)	5.6 in (141 mm)	2.2 in (59 mm)
Width:	6.4 in (161 mm)	6.4 in (161 mm)	6.5 in (165 mm)
Depth:	8.3 in (211 mm)	11.5 in (293 mm)	3.2 in (81 mm)
Weight:	5.7 lbs (2.6 kg)	6.5 lbs (3 kg)	1.1 lbs (0.5 kg)

Services

Warranty: 24 months
Service: Unisys Global

Network Services

Maintenance: No preventive

maintenance required

Power Requirements

Voltage: 90 to 264 VAC @ 47 to 63 Hz (line cords ordered separately)

Consumables

Check your Unisys Direct catalog or call 1-800-448-1424 within the USA or contact your Unisys representative for international orders.

Approvals and Certifications

Safety: ETL (Conforms to

UL1950, CSA, IEC950)

EMI: FCC Part 15 Class A

European: CE Class B

For more information, contact Unisys Payment Systems at http://www.unisys.com/marketplace/products/psd

Specifications are subject to change without notice Unisys is a registered trademark of Unisys Corporation.

All other brand names and product referenced herein are acknowledged to be trademarks or registered trademarks of their respective holders.

