

200 dpl). This statement stood true as of October 2007





fi-6140/fi-6240

High Performance Color Duplex Scanners

The Fujitsu fi-6140 and fi-6240 scanners bring high performance and advanced features in a compact design

In addition to the fi-6140 scanner being the smallest scanner in its class, both models are able to scan an impressive 60 pages or 120 images perminute in Monochrome or Grayscale (Letter @ 200dpi) as well as 40 pages or 80 images per-minute in Color (Letter @ 300dpi). Furthermore, the Fujitsu fi-6140 and fi-6240 models are the first scanners in their class to adopt high-end "fi series" functions such as:

- Paper Protection technology: Protects valuable documents by halting the scanning process when it recognizes that a jam is about to occur.
- Intelligent MultiFeed Function (iMFF): Simplifies pre-scanning preparation and improves efficiency by ignoring documents that trigger false multi-feed alerts such as an attached receipt or sticky note.
- Intelligent Capture Correction Function (iCCF): Auto-color recognition, autosize detection, and auto de-skew correction provides dramatic efficiency by combining fast scanning with simultaneous high speed image processing.

Along with ultrasonic double-feed detection, long document scanning (up to 10 feet), dual interfaces (ultra SCSI and USB 2.0), and embossed card scanning, these scanners can continuously feed up to 3 hard cards (up to 1.4 mm thick) through the Auto Document Feeder (ADF).

Fully Loaded One Box Solution

The Fujitsu fi-6140 and fi-6240 scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for the Fujitsu Advance Exchange Program, provides peace-of-mind. For full details on the Limited Warranty and on all Fujitsu service programs, go to www.lmageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.







To order or for more information:

Tel: 1-800-666-2980

E-mail: Sales@unilinkinc.com
Web: www.unilinkinc.com

Toohnical Occ	ifice	tiono				
Technical Specifications						
Model			fl-6140/fl-6240			
		fi-6140		Color Charge Coupled Device (CCD) x 2		
		fl-6240	Color Charge Coupled Device (CCD) x 3			
Light Source			White cold cathode discharge lamp			
Optical Resolution			600 dpl			
Output Resolution ¹		Color (24 bi				
		Grayscale (8 bit)		(adjustable by 1 dpi increments, 1200 dpi) ²		
Output Format Monochrome			e Color: 24 bit, 8 bit/4 bit; Grayscale: 8 bit, 4 bit; Monochrome: 1 bit			
AD Converter			1024 levels (10 bit)			
Scanning Speeds				1024 104018 (10 big		
			Simplex Duplex			
, , , , , , , , , , , , , , , , , , , ,		,		40 ppm 80 ipm		
Color ⁴		300 dpi 40 pp			80 ipm	
Grayscale ⁴ /		200 dpi	60 pp		120 ipm	
Monochrome		300 dpi	40 ppm		80 ipm	
ADF Capacity ⁵				heets (letter/A4, 20 lb.)		
	ADI	ADF minimum		2 in. x 3 in. (52mm x 74mm)		
Document size	-	ADF maximum		8.5 in. x 14 in. (Legal)		
		Flatbed (fl-6240				
ADF Feeding	Nor	Normal		11 to 56.2 lb. (41 to 210g/m²)		
Paper Weight	A8	A8 sheets		34 to 56.2 lb. (127 to 210g/m²)		
(Thickness)	Car	Card ⁶ (1.4mm) ⁷		Portrait and Landscape feeding ⁸		
Interface ⁹			Ultra SCSI (50m) / Hi gh Speed USB 2.0			
Physical Specifications						
Power requirements (auto-switching) 100 – 240 VAC, 50/60 Hz						
Power consumption		fl-6140	42W or less (Sleep: less than 6.2W)			
		fi-6240	28 – 34 W, Energy saving mode: 12 W			
Dimensions		fi-6140	11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)			
(WxDxH) ¹⁰		fl-6240	, ,			
Weight		fl-6140				
11-6240		19.36 lb. (8.8 kg)				
Environmental compatibility		ENERGY STAR® and RoHS				
Operating Temperature		42° to 95° F (5° to 35° C)				
Environment Relative humidity						
Inbox Contents			_	TWAIN, ISISTM, USB cable, AC adapter		
Bundled Software			Adobe® Acrobat® Standard, Kofax® VRS® 4.x Professional and ScandAll Pro			
Options				Software IPC, Imprinter, (Flatbed Cover Black Background for fl-6240)		
OS Support			Micr Micr	Microsoft® Windows® 2000 Professional / Microsoft® XP (32 bit/64 bit) / Microsoft® Windows Server™ 2003 (32 bit/64 bit) /		
Feed Detection Features			Ultra	Microsoft® Windows Vista TM (32 bit/64 bit) Ultrasonic Double Feed Detection Sensor Paper Protection Sensor		
1 cod Detection 1 catures			Intel	Intelligent Multifeed Function Ultrasonic Double Feed Detection, Intelligent Multi-Feed Function (IMFF),		
Other Features			Pape Long Auto	Paper Protection Function, Embossed Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction, Selectable White & Black Background (In ADF only).		
Limited Warranty				One-year. Advance Exchange program also available; restrictions apply. For full details, visit www.lmagingService.com or call (800) 626-4686.		
Service Options			Post	Post-Warranty: Advance Exchange Plus; restrictions apply.		
				Consumables: ScanAld™ kit. For full details, visit www.lmagingService.com or call (800) 626-4686.		
Part Number		fl-6140	PA03540-B005			
, sat Humbyl		fl-6240	PA03540-B505			

- Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
- Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpl or higher).
- 3. Actual scanning speeds are affected by data transmission and software processing times.
- 4. JPEG compressed figures.
- Maximum capacity varies, depending upon paper weight.
- 6. Supports ISO7810 embossed cards
- Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).
- 8. Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feeding.)
- 9. Ultra SCSI interface cannot be used simultaneously with USB2.0.
- 10. Excluding the ADF paper chute and stacker





ADOBE ACROBAT 9 STANDARD