

• Scanner Central Admin Software for Fleet Management



fi-7160 & fi-7260

Designed for workflow efficiency and built to last, the Fujitsu fi-7160 and fi-7260 scanners offer exceptional return on investment (ROI) through increased scanning speeds and reduced operator intervention.

Scanning Performance

With duplex scanning speeds of 120 images per minute at 300 dpi in Color, Grayscale, and Monochrome, the fi-7160 and fi-7260 protect your documents with acoustic sensors, ensure your data is captured with smart ultrasonic technology, and reduce rescans by cleaning up documents automatically in a single pass. Reliability is enhanced even further with new skew prevention technology for exceptional paper

- · Rapid power up time in less than 4 seconds.
- · Hard and embossed credit card scanning up to 1.4mm thick
- · Scan sticky notes, taped receipts, and labels while securing against multifeeds
- Long document support up to 18.3 feet in PaperStream IP
- · Latest USB 3.0 for forward compatibility
- 32/64 Bit Driver for PaperStream IP (TWAIN & ISIS)

Fleet Management

Bundled with fi-7160 and fi-7260, the Scanner Central Admin provides IT departments an efficient way to manage medium to large scanner deployments. With remotely

accessible fleet information, IT departments can now allocate resources effectively based on scan volume, consumable wear, depreciation schedules and maintenance expiration.



Included with Scanner

Fujitsu fi-7160 and fi-7260 scanners have everything needed to integrate with thousands of software applications in the market or with PaperStream Capture, an advanced yet easy to use scanning application provided in the box.

- PaperStream IP Image Cleanup (TWAIN & ISIS)
- · PaperStream Capture batch scanning and PDF creation software
- · One-year Advance Exchange Limited Warranty

Accessories & Options

The following options are available for purchase:

- Training & Installation to get the most out of the equipment
- Advanced Exchange Warranties in multi-year bundles
- ScanAid Kit with consumables and cleaning supplies
- fi-7160 Post-Imprinter for backside endorsing
- Black Background for fi-7260 flatbed auto-cropping
- · Carrier Sheet for double letter stitching

For full details on the Limited Warranty and other service programs, please go to www.lmagingService.com or call (800) 626-4686.











i ecililicai 3	pecilic	ations			
Models			fi-7160 (ADF only) / fi-7260 (ADF+Flatbed)		
Image Sensor Type			Color CCDs (Color Charge Coupled Device)		
Light Source			White LED Array		
Optical Resolution			600 dpi		
Output Color (24 bit)					
Output Resolution ¹	_	scale (8 bit)	50 to 600 dpi, 1200 dpi ²		
Output Color Depth		Color: 24-bit; Grayscale: 8-bit; Monochrome: 1-bit			
Internal Video Processing			65536 levels (16-bit)		
Image Processing Function			Hardware Deskew, cropping		
			Software	Multi-image, Blank page skip, i-DTC, Advanced-DTC, Simplified-DTC, sRGB, Auto color, Deskew cropping, Punch thole removal, Tab cropping, Upper lower separation, Error diffusion, Dither, Moire removal, Image Emphasis, Color cleanup, Dropout color (None, Specified, Color Saturation), Edge repair, Vertical Streaks Reduction	
Performance					
Scanning Sp (A4, Portrait)	000 0	olor ⁴ , rayscale ⁴ ,	ADF		Simplex: 60 ppm, Duplex: 120 ipm (200dpi/300 dpi)
(A4, FUITIAIL)	M	onochrome	Flatbed (fi-	-7260)	1.7 seconds (200 dpi)
ADF Capacity 5			80 Sheets (Letter 20 lb. or A4: 80 g/m²)		
	ADF m	iinimum	2 x 2.13 in. (50.8 x 54 mm)		
Document size	ADF m	aximum ⁶	8.5 x 14 in. (216 x 355.6 mm)		
	Long o	locument	8.27 x 220 in. (18.3') (210 x 5,588 mm) ⁷		
	Flatbed (fi-7260)		8.5 x 11.69 in. (216 x 297 mm)		
ADF Feeding	Le	etter	7.2 to 110 lb. (27 to 413 g/m²)		
		3 sheets	34 to 56 lb. (127 to 209 g/m²)		
		ard ⁸	Up to 1.4 mm (portrait / landscape) 9		
Interface			USB 3.0 (backward compatible)		
Physical Sp	ecifica	tions			
Power requirements			100 to 240VAC ±10%		
Power consumption (Operating)		fi-7160	38 W or less (Sleep: 1.8 W; Standby: 0.35 W) 10		
		fi-7260	41 W or less (Sleep: 1.8 W; Standby: 0.35 W) 10		
Dimensions		fi-7160	11.8 x 6.7 x 6.4 in. (300 x 170 x 163 mm)		
(WxDxH) 11 fi-7260		11.8 x 22.7 x 9.2 in. (300 x 577 x 234 mm)			
Weight —		fi-7160	9.26 lb. (4.2 kg)		
11-7260		19.4 lb. (8.8 kg)			
Environmental compatibility 12		ENERGY STAR® / RoHS / EPEAT Silver			
Operating		erature	42° to 95° F (5° to 35° C)		
Environment	Relat	ive humidity	20% to 80% (non-condensing)		
Inbox Contents			ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM, Getting Started Guide		
Bundled Software			PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi Series, Scan to Microsoft SharePoint, ABBYY FineReader for ScanSnap, Scanner Central Admin Agent.		
Options			Post-scan Imprinter (fi-7160 only), Carrier Sheet, Black Document Pad (fi-7260 only)		
OS Support			Windows® 8 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows XP® (32-bit/64-bit), Windows Server® 2008 (32-bit/64-bit), Windows Server® 2012 (64-bit)		
Feed Detection Features			Ultrasonic Double Feed Detection Sensor, Acoustic Paper Protection Sensor, Intelligent Multi-Feed Function (Manual Bypass)		
Other Features			Embossed Card Scanning Capability, Long Document Scanning, Scanner Central Admin management, USB 3.0 Support, Acoustic Paper Protection, Automatic: Color Recognition, Paper-Size Detection, De-skew Correction		
Limited Warranty			One-year. Advance Exchange program also available; restrictions apply. For full details, visit www.lmagingService.com or call (800) 626-4686.		
Service Options			Post-Warranty: Advance Exchange Plus; restrictions apply. Consumables: ScanAid™ kit. For full details, visit www.lmagingService.com or call (800) 626-4686		
Part Number		fi-7160	PA03670-B055		
rari Number		f: 7000	DA00070 DEEE		

1 Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex. 2 Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dp or higher). 3 Actual scanning speeds are affected by data transmission and software processing times. 4 JPEG compressed figures. 5 Maximum capacity varies, depending upon paper weight. 6 Document sizes larger than A4, but not exceeding A3, can be scanned (single-side) using an optional carrier sheet. 7 The scanning of documents that exceed 34 inches in length will be limited to using PaperStream IP at 200 dpi or less, 300 dpi is 215 inches. 8 Supports ISO7810 embossed cards. 9 Capable of scanning by 0 3 cards at a time. (Note: does not support multi-embossed card feeding.) 10 fi-7160 only. 11 Excluding the ADF paper chute and stacker. 12 PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2002/95/EC).



fi-7260

Technical Specifications



PA03670-B555



This scanner is designed to digitize materials that can be reproduced lawfully, in accordance with applicable copyright regulations and other laws. This product is a green product and Fujitsu promotes recycling for the scanner. Users are solely responsible for how they use this scanner. It is imperative that users comply with all applicable local rules and laws, including, without limitation, copyright laws when using this scanner

For More Information, or to Order: www.UniLinkinc.com • 800.666.2980 • Sales@UniLinkinc.com

