

## IJ6080 INKJET RECEIPT/VALIDATION PRINTER



- **2ND GENERATION MODEL**
- **NEW AND IMPROVED**
- **WITH ADDED FEATURES**
- **FOR IMAGING ENHANCEMENT**

### THE WORLD'S SMALLEST RECEIPT/ VALIDATION PRINTER!

Ideal for banks utilizing downstream image capture, the image-enhanced IJ6080 includes features designed to improve recognition rates and reduce the cost of handling reject items. This is accomplished through proprietary methods used to increase print contrast and consistency. An optional feature allows the use of pre-printed receipt stock for printing image enhanced high quality customer receipts that are ideal for marketing your brand and products. With a variety of user configurable print modes, many of the IJ6080's features can be accessed without software modification. For maximum flexibility, the IJ6080 may be configured with both a USB and serial port, or two serial ports. An OPOS driver is available.

### SPECIFICATIONS

|                             |  |
|-----------------------------|--|
| Print Method:               | Thermal Inkjet Cartridge • HP C6602A   |
|                             | Up to 7,000,000 characters (font dependent)  |
| Print Characteristics:      | Resolution: 96 x 144 dpi • Character Height: 0.125"                                  |
|                             | Character Set: Code Page 850   |
| Fonts:                      | Standard • Large • Large Bold • Times Roman • OCR-A                                  |
| Print Modes:                | Double-Wide • Single-Wide • Uni-Directional •  |
|                             | Bi-Directional • Normal • Upside-Down  |
| Receipt Characteristics:    | Paper Roll Width: 3" (76 mm) • Line Spacing: 5.5 lines per inch                      |
| Characters Per Line:        | 32 - 42 (font dependent)   |
| Validation Characteristics: | Horizontal Field: 2.8" • Top Line: 1.5" (from bottom of form)                        |
| Line Spacing:               | 6.6 lines per inch • Number of Lines: 8  |
| Print Speed:                | Characters Per Second (peak): 375 • Line Feed: 5.0" per second                       |
| Throughput•:                | 1.2" per second  |
| Interface:                  | 2 Interface Ports Provided (choose from): RS232 (2) • Parallel + RS232 • USB + RS232 |
| Baud Rate:                  | 9,600 • 38,400   |
| Microprocessor:             | Intel 80C251   |
| Memory:                     | Code (downloadable): 128K x 8 Flash • Data: 32K x 8 Ram                              |
| Code Emulation:             | Epson • Axiohm • IBM • DH • others by request  |
| Dimensions:                 | Width: 6.5" • Depth: 6" • Height: 3.4"   |
| Shipping Weight:            | 5.45 lbs. with accessories   |
| Power Source:               | 24 Volt @ 600ma (external) • Supplied with printer                                   |
| Power Consumption:          | Operating: 12 watts • Standby: 2 watts   |
| Operating Environment:      | 10 degrees to 40 degrees C • 10% to 90% RH (non-condensing)                          |
| Options:                    | Automatic Form Positioning • Black Cover   |

•Throughput is time to print benchmark 6" receipt.

Actual print speed may vary based on print requirements.

Specifications subject to change without notice.

A complete and current specification is available at [www.addmaster.com](http://www.addmaster.com)

©2005 Addmaster Corporation

Shown with optional black case

**For more Information contact us at 1-800-666-2980, or visit our website at [www.unilinkinc.com](http://www.unilinkinc.com)**