



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

IJ6160 INKJET VALIDATION PRINTER



- QUIET
- COMPACT
- USER-FRIENDLY
- TROUBLE-FREE
- ENERGY-EFFICIENT

The IJ6160 validation printer is the most compact and easy to use teller printer of its kind. Only 39 square inches, the IJ6160 handles a variety of bank forms which drop in the full-length validation slot with ease. An integrated form rack is provided to keep forms close at hand. An optional form positioning feature controls the location of printing on the form. A long-lasting inkjet print cartridge provides high quality print with consistent contrast. The IJ6160 is intended for banks using cut-form receipts and electronic journaling where a roll-paper receipt or journal tape is not required. The IJ6160 may be configured with both a USB and serial port, or two serial ports.

SPECIFICATIONS

Print Method:	Thermal Inkjet Cartridge • HP C6602A Up to 7,000,000 characters (font dependent)
Print Characteristics:	
Resolution:	96 x 144 dpi • Character Height: 0.125"
Graphics Capability:	Logos, Barcodes, OCR-A
Validation Characteristics:	
Horizontal Field:	2.8" • Top Line: 1.5" (from bottom of form)
Line Spacing:	6.6 lines per inch • Number of Lines: 8
Print Speed:	
Characters Per Second (peak):	375
Interface:	2 Interface Ports Provided (choose from): RS232 (2) • Parallel + RS232 • USB + RS232
Baud Rate:	9,600 • 38,400
Microprocessor:	Intel 80C251
Memory: Code (downloadable):	128K x 8 Flash • Data: 32K x 8 Ram
Code Emulation:	Epson • Axiohm • IBM • DH • others by request
Dimensions:	Width: 6.5" • Depth: 6" • Height: 3.4"
Power Source:	24 Volt @ 600ma (external)
Power Consumption:	Operating: 12 watts • Standby: 2 watts
Operating Environment:	10 degrees to 40 degrees C • 10% to 90% RH (non- condensing)
Options:	Automatic Form Positioning • Black Cover • Gray Cover

Specifications subject to change without notice.

A complete and current specification is available at www.addmaster.com

© 2005 Addmaster Corporation

For more Information contact us at **1-800-666-2980**, or visit our website at www.unilinkinc.com