



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

Kodak i30 and i40 Scanners



Get everything you want from a small desktop scanner—and more

Kodak i30 and i40 Scanners offer easy setup and integration, fast scanning speed and a USB 2.0 interface for quick image transfer. Plus you get great image quality with Perfect Page scanning, a Kodak exclusive.

You want fast

- Scan up to 25 pages—or 50 images—per minute
- Select up to nine assigned scanning applications (such as Kodak Capture Desktop Software) at the touch of a button
- Automatic image cropping and straightening means outstanding image accuracy at full scanning speed

You want easy

- Easy to use and fit in any work space
- A unique special document feeder on the i40 model allows front-feed, front-return scanning of small documents such as drivers' licenses and insurance cards
- Flexible electronic color dropout automatically suppresses non-critical red, green or blue background to improve forms processing
- Reliable multi-feed detection for better scanning productivity
- VRS compatible for more imaging options

You want great images

- Get renowned image quality from Perfect Page scanning—advanced image processing that allows you to scan even poor-quality documents at full speed and get exceptional images

- Five output options let you choose between color, bitonal or grayscale output or two dual stream output options: bitonal and grayscale or bitonal and color
- Customize color output to fit your application



Kodak Service & Support

Our team of service experts is here for you around the clock and around the world.



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

Kodak i30 and i40 Scanners

Recommended Daily Volume	Up to 1,000 pages per day	
Throughput Speeds (portrait, letter size)	Bitonal/grayscale: Up to 25 ppm/50 ipm at 200 dpi Color: Up to 25 ppm/50 ipm at 150 dpi; up to 25 ppm/40 ipm at 200 dpi (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.)	
Scanning Technology	i30: Single CCD; i40: Dual CCD; Grayscale output bit depth is 256 levels (8-bit) Color capture bit depth is 48 bits (16 x 3); Color output bit depth is 24 bits (8 x 3)	
Optical Resolution	600 dpi	
Illumination	Fluorescent (cold cathode)	
Output Resolution	75, 100, 150, 200, 240, 300, 400 and 600 dpi	
Maximum Document Size	215 mm x 863 mm (8.5 in. x 34 in.)	
Minimum Document Size	Single-sheet feeding: 50 mm x 87.5 mm (2 in. x 3.5 in.) Multiple-sheet feeding: 87.5 mm x 125 mm (3.5 in. x 5 in.)	
Paper Thickness and Weight	ADF: 52-105 g/m ² (14-28 lb.) paper Special document feeder (i40 Scanner only): Handles documents up to 1 mm (0.04 in.) thick	
Feeders	ADF: Up to 50 sheets of 75 g/m ² (20 lb.) paper Special document feeder (i40 only): Allows front-feed, front-return single document scanning	
Multi-Feed Detection	Length detection	
Connectivity	USB 2.0	
Bundled Software	TWAIN and ISIS drivers; Kodak Capture Desktop Software	
Imaging Features	Perfect Page Scanning, adaptive threshold processing, deskew, autocrop, relative cropping, aggressive cropping, electronic color dropout, dual stream scanning, color processing tables, image edge fill, blank page removal	
File Format Outputs	TIFF and JPEG (searchable PDF with bundled software)	
Warranty (US and Canada)	One-year warranty	
Electrical Requirements	100-240 V (International); 50-60 Hz	
Power Consumption	i30 Standby: <12 Watts; i30 Running: <30 Watts; i40 Standby: <12 Watts; i40 Running: <40 Watts	
Environmental Factors	Energy Star qualified scanners; Operating temperature: 10-35° C (50-95° F) Operating humidity: 10 percent to 85 percent RH	
Acoustical Noise (operator position Sound Pressure level)	Standby mode: <46 dB(A) Operating mode: <58 dB(A)	
Recommended PC Configuration	For documents up to 356 mm (14 in.) at 400 dpi: Pentium IV, 2.5 GHz processor, 512 MB RAM For documents up to 660 mm (26 in.) at 400 dpi: Pentium IV, 2.5 GHz processor, 1 GB RAM For longer documents/higher resolutions: Pentium IV, 2.5 GHz processor, 3 GB RAM	
Supported Operating Systems	Windows Vista SP1 (32-bit), Windows XP SP2 and SP3 (32-bit), Windows 2000 Professional SP4, Windows ME (USB 1.1 support only), Windows 98SE (USB 1.1 support only)	
Approvals and Product Certifications	AS/NZS 3548 Class B (C-Tick Mark), CAN/CSA-C22.2 No. 60950 (C-UL Mark), Canada ICES-003 Issue 3 (Class B), GB4943, GB9254 (Class B), GB 17625.1 Harmonics (CCC "S&E" Mark), EN 55022 ITE Emissions (Class B), EN 61000-3-3 Flicker, EN 55024 ITE Immunity, (CE Mark), EN 60950 (TUV GS Mark), IEC 60950, CISPR 22 Class B, VCCI (Class B), CNS 13438 (Class B), (BSMI Mark), UL 60950 (UL Mark), CFR 47 Part 15 Subpart B (FCC Class B), Argentina S-Mark	
Consumables Available	Feed module, roller cleaning pads, Staticide Wipes	
Dimensions	Weight: i30: 3.6 kg (7.9 lbs.) i40: 4.1 kg (9 lbs.) Depth: 168 mm (6.6 in.) (not including trays) Width: 337 mm (13.2 in.) Height: 162 mm (6.4 in.) (not including input tray)	
Kodak Care Kits and Maintenance Agreements		
CAT No.		
8744427	2-year enhanced AUR warranty	Provides two (2) years of advanced unit replacement (AUR) next business day service from the date of scanner purchase.
8991853	3-year enhanced AUR warranty	Provides three (3) years of advanced unit replacement (AUR) next business day service from the date of scanner purchase.

To learn more:

www.kodak.com/go/i30
or www.kodak.com/go/i40

To receive email updates and special offers from the Kodak Document Imaging Team, visit www.kodak.com/go/Dlsubscribe



As an Energy Star® Partner, Eastman Kodak Company has determined that these products meet Energy Star® guidelines for energy efficiency.

Kodak

It's time for you **AND** Kodak

©Kodak, 2010. Kodak and Sidekick are trademarks of Kodak.

Specifications are subject to change without notice.

A-5813 CAT No. 138 4080 Printed in USA 1/10

Brought to you by

UniLink