

UniLink™

Canon

imageCLASS

LBP 6650dn

To order or for more information:

Tel: 1-800-666-2980

E-mail: Sales@unilinkinc.com

Web: www.unilinkinc.com



Laser Printer

- Print in black & white at **up to 35 ppm**
- **Quick First Print** provides first print time of approximately 6 seconds
- **Duplex Printing** (2-sided)
- Efficient energy saving mode; approximately **5W of energy used**
- **Advanced Print Modes** include Poster, Booklet, Watermark, and Toner Saver

- **250-sheet front-loading** paper cassette plus 50-sheet multipurpose tray; optional 500-sheet cassette
- **Single Cartridge System** for cost-efficient supplies replenishment

Product Specifications

35
Black
ppm

QUICK
1st
PRINT

Auto Duplex Print

LOW & ENERGY
EFFICIENT

250
SHEET
PAPER CASSETTE

SINGLE
CARTRIDGE
SYSTEM

Printer Specifications

Printer Type	Monochrome Laser
Print Speed	Up to 35 ppm (letter)
Duplex Print	Yes
Duplex Print Speed	Up to 16 ipm (letter)
First Print Time	Approx. 6 seconds
Warm-up Time	Approx. 10 seconds from Power On
Printer Language	UFR II, PCL 5e/6 (45 fonts), PS Level 3 Emulation (45 fonts)
Print Resolution	Up to 600 x 600 dpi; 2400 x 600 dpi quality
Halftones	256 levels
Print Modes	Poster, Booklet, Watermark, Toner Saver
Standard Print Memory	128MB (Stationary RAM: 64 MB + Expansion RAM: 64 MB)
Maximum Print Memory	320MB (Stationary RAM: 64 MB + Expansion RAM: 256 MB) ¹

Paper Handling Specifications

Standard Paper Source(s)	250-sheet cassette plus 50-sheet multipurpose tray ²
Optional Paper Source(s)	500-sheet cassette ²
Paper Output	Approx. 150 sheets (face down) ²
Paper Weight	16 to 32 lb. bond (cassette); 16 to 43 lb. bond (multipurpose tray)
Media Sizes	Letter, Legal, A4, A5, A6, B5, Executive
Media Types	Plain Paper, Heavy Paper, Transparency, Label, Index Card, Envelope, Postcard
Envelope Capacity	5 envelopes
Envelope Types	Com 10, Monarch, DL, C5, ISO-B5

Connectivity & Software Specifications

Standard Interface(s)	USB 2.0 Hi-Speed, 10/100 Base-T Ethernet
Embedded Web Server (Remote UI)	Yes
Network Protocols	TCP/IP v4, TCP/IP v6, Apple Talk, SMB
Operating Systems	Windows® 7, Windows Server® 2008, Windows Vista®, Windows Server 2003, Windows XP/2000 Mac® OS X 10.4.9 & up, Citrix MetaFrame

Drivers available for download from www.usa.canon.com

General Specifications

CPU	333MHz
Dimensions	15.8" (W) x 14.9" (D) x 10.6" (H)
Unit Weight	25.6 lbs. (w/o cartridge); 27.4 lbs. (w/cartridge)
Warranty	1 year limited exchange warranty ³ (Extended warranty available)
Cartridge 119	Yields approximately 2,100 pages based on ISO/IEC Standard
Cartridge 119 II (Hi-Capacity)	Yields approximately 6,400 pages based on ISO/IEC Standard
Cartridge Type	Single Cartridge System
LCD Display	16 characters x 1 line
Power Consumption	1120W (Max); 5W (Energy Saver Mode)
Duty Cycle	Up to 50,000 pages per month
Security	SNMPv3, IP Filtering, MAC Address Filtering

Features and specifications are subject to change without notice.

¹ Additional print memory can only be inserted into the RAM Expansion Slot on the printer. This will require replacing the RAM already in the RAM Expansion Slot. Accordingly, when 128MB of RAM is added, RAM capacity will be extended to 192MB (Stationary RAM: 64MB + Expansion RAM: 128MB) and when 256MB of RAM is added, RAM capacity will be extended to 320MB (Stationary RAM: 64MB + Expansion RAM: 256MB)

² Based on 17 lb. bond paper.

³ Warranty program is subject to certain conditions and restrictions. See the warranty card for details.

Canon
image*ANYWARE*