LS 100 Compact and User Friendly

Compact

Quiet

Powerful

The smallest, fully-featured scanner for teller and remote deposit capture applications — lightweight and packed with features you won't find anywhere else in its class.

The LS100's compact design makes it ideal for efficient teller and remote deposit capture — fitting any space from a small desk or bank teller station to a small business or merchant environment.

- Fast front and rear check imaging — in one pass
- Vertical single feed — easy and reliable document insertion
- Output pocket for up to 20 items — increases throughput
- Auto feed option at 52 documents per minute — efficient processing
- Magnetic MICR reading — accurate code line recognition
- Rear ink-jet endorsement — programmable text
- Self-inking front stamp — avoids duplicate processing
- Magnetic stripe reading — for IDs and card payments
- Supported OS and Drivers — Windows, Linux and TWAIN
- Supported OS and interfaces — Windows 32 and 64 bits, Linux, USB, LSconnect (Ethernet), TWAIN, Ranger

LS 100 CTS UniLink

Small in Size. Big on Quality.

The LS100 is the smallest check scanner on the market with the biggest impact. Compact and quiet, robust and powerful — for any teller or merchant application.

STANDARD FEATURES
- Manual document feeder — output pocket holds up to 20 documents
- CMC7/E13B auto detect MICR reader
- Software OCR-A numeric, OCR-B, and barcode recognition (Code 39, 128, 2/5)

IMAGE CAPTURE
- Single pass, front/rear image scanning
- Bi-tonal or 16/256 grayscale rendition at 100 or 200 dpi
- Image formats supported: BMP, JPEG, TIFF, TIFF Group IV

OPTIONS
- Automatic document feeder with double feeding detection
- High definition ink-jet printer for variable rear endorsement — standard HP® cartridge
- Magnetic stripe reader (Track: 1&2 or 2&3)

COMMUNICATION & SOFTWARE
- LS Common API/DLL; Exerciser and diagnostic application
- USB 2.0 and optional USB hub with one additional host port
- Silver Bullet Ranger and TWAIN
- Optional Ethernet connectivity for LAN or thin client applications (LSconnect)
- Operating systems supported: Windows 2000/XP/Vista/Windows 7 (32/64 bit), Linux

SUPPORTED DOCUMENT CHARACTERISTICS
- Height: 1.97-4.17 in.   Length: 3.94-8.5 in.
- Thickness: 0.003-0.004 in.
- Weight: 0.01-0.02 lbs/sqf

SCANNER SIZE AND WEIGHT
- Height: 6.30 in.   Width: 4.92 in.   Length: 8.46 in.
- Weight: 4.4 lbs.

Windows, Vista, Linux, TWAIN, Silver Bullet Ranger, and HP trademarks are the property of their respective owners.

For more information, please contact:

UniLink

Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980