

LS150-VE The Speed of Silence



Quiet

Known for its speed of silence and quiet performance, convenience now joins the LS150 family. New streamlined mechanical structure and optimised electronics make this compact yet durable device the industry benchmark for high volume teller, mid-volume back office branch and remote deposit capture applications.

Fast

The LS150-VE has the smallest footprint / throughput ratio on the market today. A true value proposition in terms of robustness, performance and price, coupled with its sleek design, make it the superior choice for teller, branch, and high volume Remote Deposit Capture applications.

Compact

- Smallest footprint on the market - compact space-saver
- Up to 70 dpm
- Noise-reduction design - quiet performance
- Automatic and auto sensing input feeder - easy and reliable
- Single handed item insertion - maintain eye contact with your customer
- 50-item feeder, 120-item pocket - with convenient bin full sensor
- Bypass feeder - for image-only documents and Ids
- Supported OS and Drivers - Windows, Linux and TWAIN

LS150-VE



www.ctsgroup.it



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com



The Speed of Silence

The LS150-VE represents the best value proposition on the market today. Based on the solid mechanical design of LS150, guarantee of robustness and durability, savvy users can now benefit of the new simplified input feeder and streamlined electronics, combined in a sleek and compact shape, that make the LS150-VE a champion in price/performance.

STANDARD FEATURES

- 70 dpm throughput
- Image and ink jet endorsement
- Automatic and auto-sensing input feeder
- 50 item feeder - up to 120 item pocket
- Pocket-full sensor
- CMC7/E13B auto detect MICR reader
- Software OCR-A, OCR-B, and barcode recognition (Code 39, 128, 2/5 and PDF417)
- Bypass feeder - for image-only documents and ID card
- Virtual endorsement available

IMAGE CAPTURE

- Single pass, front/rear image scanning
- Bi-tonal or 16/256 grayscale rendition at 100, 200, 300 dpi
- Image formats supported: BMP, JPEG, TIFF Group IV

OPTIONS

- One line 12 Nozzle rear inkjet printer
- Standard HP® high resolution cartridge with approx. 6,000,000 characters life
- Rotational, self-inking front stamp, rechargeable each 60,000 + items
- Magnetic stripe reader (Tracks 1, 2, 3)

COMMUNICATION & SOFTWARE

- USB 2.0
- LS Common API/DLL; Exerciser and diagnostic application
- Silver Bullet Ranger
- TWAIN
- Operating systems supported: Windows 2000, XP, Vista (32/64 bit), Linux

SUPPORTED DOCUMENT CHARACTERISTICS

- Height: 60-108 mm (2,4 - 4,3 in)
- Length: 80-225 mm (3,2 - 8,8 in)
- Thickness: 0,07-0,12 mm (0,003-0,005 in)
- Weight: 70-120 g/sqm (0,001-0,002 lbs/sqf)

SCANNER SIZE AND WEIGHT

- Height: 175 mm (6,9 in) Width: 140 mm (5,5 in) Length: 230 mm (9,0 in)
- Weight: 3,5 Kg (7,7 lbs)

Windows, Vista, Linux, TWAIN, Silver Bullet Ranger, and HP trademarks are the property of their respective owners.



Since 1980, CTS has been a leading manufacturer of cash and check solutions with 1,000,000+ banking peripherals and over 150,000 scanners installed across five continents. Our expertise includes: Document Processing Devices, Card Personalization Printers, OEM Modules and Dispensers, Cash and Coin Recycling and Processing Systems.

LS150-VE