For More Information, or to Order: Unilink

www.UniLinkinc.com 800,666,2980 Sales@UniLinkinc.com

## MT30 Multi-Media Terminal

PAX's MT30 is a fully featured customer-facing, multimedia POS device which offers retailers an innovative branding channel. Combining high-security payment, outstanding durability and PCI compliance, the MT30 features a responsive capacitive touch screen and electrostatic pen to enable electronic signature capture and excellent finger touch responsiveness.

Consumers can enter their PINs using the tactile keypad, protected by an integrated privacy shield. Optional signature capture capability allows retailers to streamline transactions.

PAX's MT30 is the perfect platform to deploy value-added branding and messaging.



MT30

# MT30 Multi-Media Terminal

### FEATURES & BENEFITS



- PCI PTS 2.1 approved
- High speed ARM 11 processor
- Large memory capacity
- 4.3" color screen, projective capacitive touch panel
- Fast transactions PLUS the creative use of rich media
- Cost-effective, highly durable
- Supports EMV, Magnetic stripe and Signature Capture
- Multi-port functionality: RS232, USB, LAN

## **SPECIFICATIONS**

#### Processor

32-bit ARM11

#### Memory

192MB (128MB Flash, 64MB DDR RAM) Micro SD (TF card) up to 32GB

#### Display

4.3 inch 480 x 272 pixels color TFT LCD Projective Capacitive Touch Panel with stylus

#### Keypad

PCI PTS 2.1 approved ADA style keypad 10 numeric & 3 function keys

#### **Magnetic Card Reader** Track 1/2/3, bi-directional

**Smart Card Reader** EMV L1 & L2 certified

#### **Card Slots**

4 SAMs or 3 SAMs, 1 SIM or 2 SAMs, Dual SIM

Communication Ethernet

### **Peripheral Ports**

2 x RS232, 1 x LAN 1 x Mini USB (OTG)

#### Security

DUKPT, Master/Session, 3DES ANSI/ISO9564 format 0, 1, 3 PIN ciphered key algorithm ANSI X9.9/X9.19 MAC algorithm

#### Environmental

0°C to 50°C (32°F to 122°F) operating temperature 10% to 90% relative humidity, non-condensing -20°C to 70°C (-4°F to 158°F) storage temperature

Voltage Input: 100~240VAC, 50Hz/60Hz, 0.5A Output: 12VDC,1A

### For More Information, or to Order:



www.UniLinkinc.com 800.666.2980 Sales@UniLinkinc.com



THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY, ALL FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries.

All other trademarks or brand names are the properties of their respective holders. Copyright 2014, PAX Technology Limited, All Rights Reserved.

Physical

Length: 257mm Width: 178mm Height: 58 mm

Weight 707g

## Certification

PCI PTS 2.1 EMV L1 & L2