

For more information, or to order:



UniLinkTM
www.UniLinkinc.com
800.666.2980
Sales@UniLinkinc.com

SmartSource ReceiptNOW[®]



SmartSource
ReceiptNOW Elite



SmartSource
ReceiptNOW

Our Customers Say it Best!

“Integrating the ReceiptNOW printers and SmartSource scanners enabled us to deliver an enhanced client experience while capitalizing on processing efficiencies.” – Rachel Emery, AVP Office Automation Manager, United Bank & Trust

SmartSource ReceiptNOW

Prints receipts right at your check scanner. Engineered to fit under Burroughs SmartSource scanners – combining scanner and receipt printer units into one footprint, saving valuable counter space!

SmartSource ReceiptNOW — Designed to fit under the SmartSource Professional, Value, Expert, Adaptive, and other scanners.

SmartSource ReceiptNOW Elite — Engineered to fit beneath the SmartSource Elite series scanners.

Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Largest paper roll
- Full or partial paper cut

- Fast 8 inches/second (20 cm/second) delivery
- Less maintenance than matrix printers
- Fast installation for existing sites
- Three year warranty (advanced exchange available)

Compatibility

- USB or Ethernet (ReceiptNOW only) interface
- Full 108 std & international fonts w/barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- Worldwide certifications

Customizable Teller Receipts

- Top/bottom logos
- Border messages
- Watermarks
- Windows True Type fonts
- Color text/graphics – using 2-color paper



For More Information, or to order:

UniLink • 800.666.2980 • www.UniLinkinc.com • Sales@UniLinkinc.com

SmartSource ReceiptNOW Technical Information



Models

SRNELITE-USB – ReceiptNOW Elite, USB Interface
SRN2PTR-USB – ReceiptNOW, USB Interface
SRN2PTR-ETH – ReceiptNOW, Ethernet Interface

Printing/Feed/Cut

Direct Thermal Printer
Black and Two Color Capability
Black Print Speed 8 inches/second (20 cm/second)
Resolution: 203 x 180 dpi
95 Alphanumeric, 13 International Characters w/Kanji
True Type Fonts available when being driven as a Windows printer
1D/2D Bar Code Fonts
512K on-board Logo Flash
Full/Partial Auto Cutter

Controls

On/Off Switch
Paper Empty/Low LED's w/Audible Alerts
Paper Feed Button
Paper Width Adjustment
Power indicator

Interface

USB or 10/100 Base-T/TX
Standard ESC/POS Command Set
OPOS & JavaPOS, Auto Status Back (ASB)

Dimensions

	ReceiptNOW	ReceiptNOW Elite
Height:	5.4 inches (13.7 cm)	5.2 inches (13.2 cm)
Width:	15.3 inches (38.8 cm)	9.5 inches (24.2 cm)
Length:	6.1 inches (15.5 cm)	5.7 inches (14.5 cm)

Environment/Acoustics

5~50°C Operating Environment
Acoustics < 60 dba Cutting or Printing

Power

International Power 100-240VAC, 50/60Hz
Power Supply Included

Paper/Loading

Standard, Security, Non-BPA, 2-Color Paper
2.4 in. to 3.25 in. (6.1 cm to 8.3 cm) Paper Widths - Adjustable
Largest 3.25 in. (8.3 cm) Diameter Paper Roll
Slide Out Tray, Drop-in Paper

Warranty/Service

3 Year Warranty
Advanced Exchange Available

Graphic Receipt Customization

Multiple Graphics Can be Placed Anywhere
Custom Messages
Watermarks

Host OS

Win 2000, XP, Vista (32/64), Windows 7 (32/64), Windows 8 (32/64)

Maintenance

Print Exerciser & Diagnostic Software
Operator Guide

Certifications

FCC Class B, CE, VCCI, for EMI Emissions
CE, for Susceptibility and ESD
CE, CB, CUL/UL 60950, for Safety
RoHS Compliant (EU)
2010 Appliance Efficiency Regulations, California, Title 20



For More Information, or to order:

UniLink

800.666.2980
www.UniLinkinc.com
Sales@UniLinkinc.com

Burroughs is a registered trademark licensed to Burroughs, Inc. in the United States and other countries. SmartSource, ReceiptNOW and Cache2Cash are registered trademarks of Burroughs, Inc. Ranger is a registered trademark of Silver Bullet Technology, Inc. All other brands and products referenced in this document are acknowledged to be the trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.



SmartTIP For more information use your smartphone and snap a photo.

