

To order or for more information:

Tel: 1-800-666-2980
E-mail: Sales@unilinkinc.com
Web: www.unilinkinc.com

ScanSnap S1100



Providing Mac and PC users the tools to be productive and paperless...anywhere.







To order or for more information:
Tel: 1-800-666-2980
E-mail: Sales@unilinkinc.com

Web: www.unilinkinc.com

SCANSIAP S1100

Deceluat Na	ma / Dort numb	00 04400 / PA00040 POOF		
Product Name / Part number		ScanSnap S1100 / PA03610-B005		
Scanner Type		Single Sheet, Simplex, Color Scanning with CDF (Continuous Document Feeding)		
Scanning M		Color, Grayscale, Monochrome, Automatic Mode Detection		
Image Sens		CIS (Contact Image Sensor) X 1		
Light Source		3 Color LED (Red, Green, Blue)		
Optical Res		600 dpl (dots per inch)		
Scanning	Auto Mode ²			
Speed 1	Normal Mode	7.5 seconds per page		
(A4 portrait	Better Mode	7.0 cooding per page		
/AC Adapter)	Best Mode			
	Excellent Mode	35 seconds per page		
Document	Normal Mode	A4, A5, A6, B5, B6, Business Card, Post Card, Letter, Legal and Custom Sizes. Max: 8.5 x 14.17 in. (216 X 360mm), Min: 1 x 1 in. (25.4 x 25.4 mm), Automatically recognizes document size		
Size	Normal Mode w/ Carrier Sheet	Use of a carrier sheet permits the scanning of A3, B4,double letter and photo- graphs as well as the document sizes that are listed above (simplex only)		
	Long Document 4	Max: 8.5 x 34 in. (216 x 863 mm) @ 300dpl or less		
Paper Weight (Thickness)		Paper: 14 to 56 lbs. (Straight path) Paper: 14 to 20 lbs. (U turn path) Card: Portrait or Landscape (Straight Path) Non-embossed: 0.76 mm or less Embossed: 0.76 + 0.48 mm (ISO7810 Conforming)		
Paper Setti	ng	Front-side up		
Interface ⁵		USB2.0 (USB1.1 Compatible)		
Software In	terface Driver ³	ScanSnap Manager (TWAIN/ISIS™ not supported on Mac or PC) ³		
Power Requ	ulrement	5V / 0.5A (1 Port)		
Power Consumption		During operation: 2.5 W or less, During sleep mode: 1W or less During power off: Less than 0.5 W		
Operation Environment		Temperature; 41°F to 95°F (5°C to 35°C) Relative Humidity; 20% to 80% (Non-condensing)		
Dimensions (W X D X H) 6		10.74 x 1.87 x 1.33 ln. (273 x 47.5 x 34 mm)		
Device Weight		12.34 ounces (0.77 lbs. or 350 grams)		
Environmental Compliance		ENERGY STAR® compliant / RoHS 7		
Limited Warranty		1 year Limited Warranty. For full details, visit www.fcpa.fujitsu.com/warranties call (800) 626-4686		
Service Options		In-warranty Upgrade: Advance Exchange. For full details on all service program visit www.lmagingService.com		

1: Scanning speeds may vary due to the system environment used. Scanning speed measured from "start feeding document" to "finish output document" after pre-pick and pressing scan button (not including warm-up time). Warm-up time is less than 2 seconds for less than 3 seconds from chute cover closed). 2: Documents measuring approximately 5.8 inches (148 mm) in length or less are scanned in "Best Mode" while other documents are scanned in "Bester Mode". 3: Devote cannot be selected as a TWAIN, ISIS®, or WIA source. Applications that require these drivers cannot be used directly. 4: S1100 is capable of scanning documents that exceed As size in length. This function is available for all modes except excellent mode. 5: PC with USB 3.0, will work as USB 2.0 guaranteed only with USB cable provided with product. 6: When chute is closed. 7: PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2002/85/EC).

Software		
Operating System	Windows®	Mac OS
Interface Software ¹	ScanSnap Manager V5.1 (TWAIN / ISIS not supported)	ScanSnap Manager V3.2 (TWAIN / ISIS not supported)
	ScanSnap Organizer V4.1	Cardiris™ 3.6 for ScanSnap
	CardMinder™ V4.1	ABBYY FineReader for ScanSnap™ 4.1
Applications	ABBYY FineReader for ScanSnap™ 4.1	Evernote for Mac 1.10
фриосионо	Evernote for Windows 3.5	
	Scan to Microsoft SharePoint® 3.4	

1: TWAIN or ISIS™ applications cannot be used directly

Options				
Description	Model Number	Remarks		
ScanSnap S1100 Case 1	PA03610-0001	Intended for S1100 and included items		
ScanSnap Carrier Sheets ²	PA03360-0013	Includes 5 individual carrier sheets for use with select ScanSnap products including S1100		

1: This product has been especially designed for storing and carrying ScanSnap S1100. Please note that this product is not guaranteed to withstand damage by excessive shock or external pressure. 2: Although ScanSnap Carrier Sheets have a listed lifespan of 500 scans, the lifespan may vary with usage. ScanSnap Carrier Sheets are intended to scan paper documents with weights of 127 g/m2 or less. They also support the scanning of folded documents that are as large as 216 x 297 mm.

әузіені нецин	rements for PC Windows			
Compatible Operating Systems		Windows® 7 (32bit/64bit)	Windows® Vista™ (32bit/64bit)	Windows® XP (32-bit only)
	ScanSnap Manager V5.1	Supported	Supported 3	Supported 4
	ScanSnap Organizer V4.1 ⁵	Supported	Supported 3	Supported 4
Interface /	CardMinder™ V4.1	Supported	Supported 3	Supported 4
Applications ^{1,2}	ABBYY FineReader for ScanSnap 4.1	Supported	Supported 3	Supported 4
	Evernote for Windows 3.5 6	Supported	Supported 3	Supported 4
	Scan to Microsoft SharePoint 3.4	Supported	Supported 3	Supported 4
	CPU 7	Intel Pentium® 4 @ 1.8GHz or higher (Intel® Core™ 2 Duo		
	0.0	2.2GHz or higher recommended)		
	Memory Capacity 7	64 Bit: 2GB or more	512MB or more	
Hardware	Welliory capacity	32 Bit:1GB or more	(1GB or more recomm	iended)
Requirements	Display	800 x 600 pixels or more, High color (16-bit) or more		
	Disk Capacity ⁸	2,470 MB or more free hard disc space for full installation		
	DVD-ROM Drive	Required for installation		
	USB Port 7	USB 2.0 / USB 1.1		

1: These applications only support Microsoft Windows®. 2: For the latest support information, visit the ScanSnap homepage. 3: Service Pack 1 or later required. 4: Service Pack 3 or later required. 5: Adobe® Acrobat® 7.0 or later (included) is required in order to use the Adobe® Acrobat® search feature. Please check the Adobe homepage to determine which version of Adobe Acrobat is supported by the OS you are using. 6: Evernote for Windows required .NET framework 3.5 SP1.7: Scanning speeds may drop if recommended CPU, memory capacity and USB 1.1 requirements are not met. 8: Unless previously installed, Microsoft .NET framework 3.5 SP1 will be installed (requires 500 MB of disk space) together with either ScanSnap Manager of SanSnap Organizer. 9: Support requirements may change depending on the duration of support and the support policy of the companies that make the software listed in the table above.

System Requirements for Mac				
Compatible Operating Systems		Mac 0S X v10.6 1	Mac OS X v10.5 ²	Mac OS X v10.4 ³
Interface /	ScanSnap Manager V3.1	Supported	Supported	Supported
Applications 4,5	Cardiris™ 3.6 for ScanSnap	Supported ⁶	Supported	Supported
Applications	ABBYY FineReader for ScanSnap 4.1	Supported	Supported	Supported
	Evernote for Mac 1.10	Supported	Supported 7	Supported
Hardware Requirements	CPU ⁸	Intel® Core™ Duo @ 1.83GHz or higher (Intel® Core™ 2 Duo 2.4GHz or higher recommended)	Intel® Core™ Duo @ 1.83GHz or higher (Intel® Core™ 2 Duo 2.4GHz or higher recommended) Power PC G5 1.6GHz or higher	
	Memory Capacity ⁸	1GB or more	512MB or more (1GB recommended)	
	Display	1024 x 768 pixels or more		
	Disk Capacity	1320MB free hard disc space for installation		
DVD-ROM Drive		Required for installation		
USB Port ⁸		USB 2.0 / USB 1.1		

1: Mac OS X v10.6.4 or later recommended. 2: Mac OS X v10.5.8 recommended. 3: Mac OS X 10.4.11 recommended. 4: These products only support Mac OS, 5: For the latest support information, visit the ScanSnap homepage, 6: Requires Rosetta. 7: Mac OS X v10.5.8 only. 8: Scanning speeds may drop if recommended CPU, memory capacity and USB 1.1 requirements are not met. 9: System requirements may change depending on the duration of support and the support policy of the companies that make the software listed in the table above.

Rack2-Filer V5.0 System Requirements (Windows® Only) for Deluxe Bundle only ²					
Compatible Operating Systems		Windows® 7 (32bit/64bit)	Windows® Vista™ (32-bit & 64-bit)	Windows® XP (32-bit only)	Windows® 2000 Professional ¹
	CPU	Intel Pentium® 4 @ 1.8GHz or higher		Intel® Pentium® III 600 MHz or higher	
Hardware Requirements	Memory Capacity	64 Bit: 2GB or more 32 Bit: 1GB or more	512MB or more (recommended: 1GB or more)	256 MB or more (recommended: 512 MB or more)	
	Display	800 x 600 pixels or more, High color (16-bit) or more			
	Disk Capacity	System drive: 10 MB or more disk space Installation drive: 450 MB or more disk space Additional space required for the data created by Rack2-Filer			er

1: Service Pack 4 or later 2: Provided only with ScanSnap S1100 Deluxe Bundle Part Number PA03610-B015

Included items

• Getting Started • Setup DVD-ROM • USB Cable (2.0 m) • Rack2-Filer (provided with ScanSnap S1100 Deluxe Bundle)

Consumables				
Description	Part Number	Remarks		
Cleaning Wipe	PA03950-0419	1 pack (24sheets) Used to clean rollers		







