


TM-S2000II Multifunction Device



Multifunction Device

POS

Versatile multifunction device for quality check scanning and printing.

Versatile multifunction device — configuration flexibility; connect via USB

LCD status updates — quick, easy access to function or maintenance status

Best warranty in its class — dedicated technical resource team; customized solutions; 2-year limited warranty

Fastest scan speeds in its class — scans up to 225 dpm

Built-in inkjet printer — up to 16 lines of printing for cashier's checks, slip sheets, endorsements and marketing graphics

2-sided ID scanning — easily capture color ID cards

Built-in cashier's check printing — print area up to 2"

Powerful productivity — 100-check document feeder

Line Inkjet Printer

Print Method Line ink, 360 nozzles
Print Resolution 180 x 180 dpi
Print Font Font A (default): 12 x 24/Font B: 9 x 17
Reliability MTBF 180,000 hours
Head Life 6 billion shots/nozzle¹

Document Scanner

Throughput Up to 130, up to 225 dpm (documents per minute)
Speed Paper feeding up to 1,000 mm/sec
Area 106 x 235 mm
Resolution 100 dpi, 120 dpi, 200 dpi, 240 dpi interpolated, 300 dpi optical
Method CIS (Contact Image Sensor)
Mode 24-bit Color, 8-bit Grayscale, Bi-tonal
Capacity Auto-input feeder of 100 items; exit pocket of 100 items; optional second pocket of 50 items
MICR E13B and CMC7
Data Compression CCITT Group 4, JPEG
Data Transmission Format TIFF, JPEG, JTIFF, BMP (Windows® bitmap), Raster (Raw)
OCR OCR-A, OCR-B and 1D Barcode
Rated Life 2 million items
MCBF 4,940,000 cycles
MTBF 180,000 hours
D.K.D. 2 drawers

ID Card Scanner

Throughput 1 at a time; multiple feeding is not available
Speed Card feeding: 118 mm/sec (600 dpi color)
Area ISO/IEC 7810 card
Resolution 300 dpi, 600 dpi
Method CIS (Contact Image Sensor)
Mode 24-bit Color, 8-bit Grayscale
Capacity 1 ID

Operating Systems

Windows 10, Windows 8/8.1, Windows 7, Windows Vista®, Windows XP, Windows XP Embedded, Windows Embedded POSReady 2009, Windows Embedded Standard 7, Windows Embedded POSReady 7, Windows Server® 2008/2008R2, Windows Server 2012/2012R2, Windows Server 2016

General Information

Factory Options USB hub 2 ports, USB specification 2.0
Second Pocket Maximum of 50 items
Single-pocket Size 206 x 263.8 x 142 mm (H x D x W) [8.11" x 10.39" x 5.59"]
Two-pocket Size 206 x 298.8 x 167 mm (H x D x W) [8.11" x 11.76" x 6.58"]
Power PS-180, 24 VDC; there is only one power supply for the scanner and printer
Weight
 One-pocket model: 3.7 kg (8.16 lb)
 Two-pocket model: 4.1 kg (9.04 lb)
Case Color Epson® Black
Environmental Standards WEEE, RoHS compliant
Warranty 2-year limited warranty
Country of Origin China

Packaging Specifications

Single Box Dimensions (L x W x H)
 15.75" x 9.85" x 11.4"/400 x 250 x 290 (mm) (weight = 5.5 kg)

What's in the Box

USB cable, dedicated ink cartridge [SJC18(K)] x 2, AC cable, AC adapter [PS-180 (Model: M159B)], Setup Guide, cut-sheet paper (starter cut-sheet paper for operation check)

Eco Features

RoHS compliant
 Recyclable product²
 Epson America, Inc. is a SmartWay® Transport Partner³

Ordering Information⁴

Scanner, 130, Single Pocket	A41CG60031
Scanner, 225, Dual Pockets	A41CG60111
Scanner, 130, Dual Pockets, USB Hub, MSR	A41CG60001
Scanner, 130, Single Pocket, USB Hub, MSR	A41CG60021
Scanner, 225, Dual Pockets, USB Hub, MSR	A41CG60101

¹ Shots are the number of electric pulses for the printhead. | ² For convenient and reasonable recycling options, visit www.epson.com/recycle | ³ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | ⁴ Contact your Epson representative for additional models.

For more information or to order, please contact:

UniLink

Sales@UniLinkinc.com | www.UniLinkinc.com | 800.666.2980