



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

EPSON

TM-U325 Printer

Compact Validation/Receipt Printer



Compact and powerful, **Epson's TM-U325** combines two printers in one: a speedy, quiet receipt printer and a multi-line validation printer. Epson's TM-U325 is the ideal choice for environments that want to reap the benefits of both a receipt printer and a validation printer — but want it all in one economical, space-saving printer.

- Receipt and validation printing in a compact body
- Quiet, 6.4 lps receipt printing speed
- Handles up to 9 lines of validation
- User-friendly features such as drop-in paper loading and Auto Status Back (ASB) messages
- Connect-It™ interfaces for system compatibility
- Renowned Epson quality, reliability, dependability

Quick and quiet impact printer

Surprisingly fast, Epson's TM-U325 logic-seeking control device allows receipts to print at 6.4 lines per second (16 digits, 16 cpi). Even more surprising, the TM-U325 delivers its printing so quietly, customers won't know it's there.

Packs a punch in small spaces

This powerful, space-saving printer measures 164 x 240 x 136mm (W x D x H) {6.46 x 9.45 x 5.35"} and weighs only 2.3 kg (approximately 5.07 lbs). Its efficient design lets you make the best use of limited counter space. Even the AC adapter power source is compact. With the TMU325 print buffer at 45 bytes, there's practically no limit to the number of downloadable fonts you can use to convey the image you want.

Epson printers define "ease-of-use"

No other company offers as many user-friendly features as Epson. Drop-in paper loading that allows busy operators to replace paper quickly. An Auto Status Back (ASB) feature monitors printer status in real-time, keeping printer operation moving and users productive.

For total compatibility, just Connect-It™

With Epson's exclusive Connect-It interface options, the TM-U325 is totally compatible with today's best-of-breed and component-based systems. Thanks to this technology, you can choose virtually any system you want or use what you already have.

Epson quality and reliability

When you choose Epson's TM-U325, you can be sure you'll get unsurpassed performance and dependability. Because, like all Epson point-of-sale products, the TM-U325 meets Epson's world-renowned standards for quality and reliability.

For more information contact us at:

1-800-666-2980

or visit our website

www.unilinkinc.com



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

Product Specifications

| | | |
|----------------------|---------------------|---|
| General | Print method | 9 pin, serial impact dot matrix |
| | Print font | |
| | Font | 7 x 9/9 x 9 |
| | Column capacity | 40 or 42 columns/33 or 35 columns |
| | Character size | 1.24 x 3.1mm (W x H)/1.56 x 3.1mm (W x H); {0.049 x 0.122"/0.061 x 0.122"} |
| | Character set | 95 Alphanumeric, 32 International, 128 x 8 Graphic |
| | Characters per inch | 16 or 17.8 cpi/13.3 or 14.5 cpi |
| Printer | Interface | RS-232C, Bi-directional parallel, Connect-It* |
| | Data buffer | 4KB/45 bytes |
| | Print speed | Approx. 3.5 lps (at 40-column printing)/approx. 6.4 lps (at 16-column printing) |
| | Paper dimensions | Maximum print lines: 9 lines |
| | Receipt | 76±0.5 x diameter 83mm (2.99±0.02 x diameter 3.27") |
| | Validation | 135 to 182 x 70 to 182mm (W x L) {5.31 to 7.17 x 2.76 to 7.17"} |
| | Paper thickness | |
| | Receipt | 0.06 to 0.085mm [0.0024 to 0.0033"]/sheet (total thickness: 0.2mm [0.079"] or less) |
| | Validation | 0.09 to 0.12mm [0.0035 to 0.0047"]/sheet (total thickness: 0.09 to 0.31mm [0.0035 to 0.012"], (including the thickness of roll paper) |
| | Copy capability | One original and two copies |
| | Inked ribbon | ERC-38 (purple, black) |
| | Ribbon life | 4,000,000 characters (purple), 3,000,000 characters (black) |
| | Power supply | AC adapter (included), PS-180 (option) |
| | Power consumption | Approx. 43W |
| | D.K.D. function | 2 drivers |
| | Reliability | |
| | MTBF | 180,000 hours |
| | MCBF | 49,000,000 lines |
| | Overall dimensions | 164 x 240 x 136mm (W x D x H) {6.46" x 9.45" x 5.35"} |
| | Mass | Approx. 2.3 kg (5.07 lbs) |
| Control Board | EMI standards | FCC class A, CE marking |
| | Safety standards | UL, CSA |

Inch values are approximate.

cpi: characters per 25.4mm (characters per inch)

lps: lines per second

Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • (562) 290-5304 • <http://pos.epson.com/financial>

©2009 Epson America, Inc. Epson is a registered trademark and Epson Exceed Your Vision is a registered logomark of Seiko Epson Corporation. CaptureOne is a trademark of Epson America, Inc. All other trademarks are the property of their respective owners. Specifications are subject to change without notice.

SD-DSCAPONEE

For more Information contact us at 1-800-666-2980, or visit our website at www.unilinkinc.com