

To order or for more information:

Tel: 1-800-666-2980
E-mail: info@unilinkinc.com
Web: www.unilinkinc.com

EPSON

TM-U375 Printer

Compact Multifunction POS Printer



Get receipt, slip, and validation printing all in one small, space saving package. The TM-U375 makes the most efficient use of limited space, and with a clamshell mechanism that simplifies roll paper replacement and a moveable platen that facilitates slip insertion, this printer also boasts excellent paper handling.

- Optimized features and small footprint perfect for busy counters
- Easy paper loading
- High speed logic seeking print head
- Save ports by using optional display interface
- OPOS compliant
- High reliability

Handles many types of media

EPSON'S high-quality multifunction printer can be used for a variety of applications. The TM-U375 prints receipts; slips, journals, and can also perform validation printing. Printing up to 58 lines on slip paper and 16 lines of validation printing, this printer handles the needs of almost any environment.

User friendly design and use

The moveable platen, paper loading lever switch and clamshell mechanism makes slip insertion, roll paper loading and routine maintenance quick and easy. The TM-U375 also includes a port to attach an optional EPSON pole display. Add to this an ASB (Automatic Status Back) function to keep

operators constantly informed of printer status.

Small footprint

With a height of just 145 mm $\{5.7''\}$ and a footprint of only 186×327 mm (W \times D) $\{7.3 \times 12.9''\}$, the TM-U375 is one of the smallest 1.5 station printers available, allowing you to use your limited counter space to its maximum efficiency.

Compatibility

The TM-U375 conforms to EPSON's ESC/POS② command system. Moreover, high expandability and easy upgradability ensure efficient use of current software assets. Also, using the EPSON OCX driver for OLE POS (OPOS) will allow you to reduce time and money spent on developing POS application software.

Superb Reliability

EPSON's world-renowned quality and reliability are reflected in every component and mechanism of the TM-U375, ensuring our products are unsurpassed in performance and dependability.

Smart technology. Smart business.

For more information contact us at:

1-800-666-2980

or visit our website

www.unilinkinc.com



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com
Web: www.unilinkinc.com

Product Specifications

Print Method 9-pin, serial impact dot matrix

Print Font $5 \times 9 / 7 \times 9$

Column capacity 33 / 40 columns

Character size

 $1.56 \times 3.1 \text{ mm (W} \times \text{H)} / 1.24 \times 3.1 \text{ mm (W} \times \text{H)}$

 $\{0.061 \times 0.122" / 0.049 \times 0.122"\}$

Character set 95 Alphanumeric characters, 32 International characters, 126 × 8 Graphic characters

Print Speed

Approx. 3.5 lps (40 columns, 16 cpi)

Approx. 5.4 lps (20 columns, 16 cpi)

Data Buffer 4 KB or 40 bytes

Interfaces RS-232C / Bi-directional parallel

Paper Dimensions

Receipts or Journal: $76 \pm 0.5 \times$ diameter 83 mm $\{2.99 \pm 0.02 \times$ diameter 3.27" $\}$

Slip: 70 to 182 \times 160 to 257 mm (W \times L) {2.76 to 7.17 \times 6.30 to 10.12"}

Validation: 135 to 182×70 to 257 mm (W × L) {5.31 to 7.17×2.76 to 10.12"}

Paper Thickness

Receipts or Journal: 0.06 to 0.085 mm / sheet {0.0024 to 0.0033"}

(Total thickness: 0.16 mm {0.0062"} or less) Slip: 0.09 to 0.12 mm / sheet {0.0035 to 0.0047"} (Total thickness: 0.09 to 0.31 mm {0.0035 to 0.0122"})

Copy Capability

Receipts or Journal: One original and one copy

Slip: One original and two copies

Inked Ribbon ERC-38 (purple, black)

Ribbon Life Purple: 4,000,000 characters, Black: 3,000,000 characters

Power Supply Voltage 24 VDC ± 10%

Current Consumption Approx. 1.4 A (mean) **D.K.D. Function** 2 drivers

Reliability

MTBF 180,000 hours

MCBF 29,000,000 lines

Overall Dimensions $186 \times 327 \times 145 \text{ mm} (W \times D \times H) \{7.3 \times 12.9 \times 5.7''\}$

Mass Approx. 4.0 kg {8.8 lb}

EMI Standards VCCI class A, FCC class A, CE marking

Safety Standards UL, CSA

Inch values are approximate.

cpi: characters per 25.4 mm (characters per inch) Specifications are subject to change without notice.

Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • (562) 290-5304 • http://pos.epson.com/financial ©2009 Epson America, Inc. Epson is a registered trademark and Epson Exceed Your Vision is a registered logomark of Seiko Epson Corporation. CaptureOne is a trademark of Epson America, Inc. All other trademarks are the property of their respective owners. Specifications are subject to change without notice.

SD-DSCAPONEE

For more Information contact us at 1-800-666-2980, or visit our website at www.unilinkinc.com