

To order or for more information:

Tel: 1-800-666-2980
E-mail: info@unilinkinc.com
Web: www.unilinkinc.com

## High-Speed Two-Color Multifunction Printer

# Epson TM-H6000III



There is only one printer that combines fast, reliable printing with innovative, time-saving features for retail and banking—Epson'sTM-H6000III multifunction printer.

The TM-H6000III offers high-speed receipt and slip printing, validation, advanced check processing and a MICR accuracy of 99.9%, all in a compact design.

#### **Quick check processing**

The ultra-reliable, ultra-fast TM-H6000III multifunction printer is the ideal printer for grocery, general merchandise and banking. With its innovative QuickPass™ technology, the TM-H6000III reads MICR and prints and endorses a check in a single pass. This shortens check printing time up to 50% over "check flipping" options, which means faster transaction and throughput times.

#### High speed and reliability

With thermal receipt printing up to 63 lines per second, the TM-H6000III offers fast, reliable printing that keeps your lines moving. And with an MCBF of 72 million lines, the TM-

H6000III is rugged enough for even the most demanding retail and banking applications.

#### **Industry-leading MICR reader**

Implementing ECC using Epson's MICR reader with 99.9% accuracy eliminates misreads and substitution errors and lowers returned check costs.

#### **Crisp two-color printing**

Epson's exclusive two-color technology prints crisp logos, coupons and graphics. And with 384 KB of non-volatile memory for the storage of graphics, there is no processing delay when printing in color.

#### Fast and easy validation

The TM-H6000III features dropin validation which allows clerks and tellers to rapidly validate a variety of forms including checks, deposit slips and batch tickets.

#### Simple to maintain

Epson's ASB (Automatic Status Back) function keeps operators informed of printer status and the built-in maintenance counter tells you when to schedule routine maintenance.

#### **Future-proof flexibility**

By utilizing our unique Connect-It™ interface modules, the TM-H6000III is compatible with IBM legacy and component-based systems, so it won't become obsolete when you update your POS systems.

For more Information contact us at 1-800-666-2980, or visit our website at www.unilinkinc.com



To order or for more information:

Tel: 1-800-666-2980 E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

## Epson TM-H6000III Multifunction Printer

### **Product Specifications**

		Receipt		Slip	Endorsement Printer <sub>1</sub>	
General		Thermal line printing		9-pin serial impact dot matrix	8-pin shuttle impact dot matrix	
	Print font	9 x 17 / 12 x 24		5 x 9 / 7 x 9	5 x 7	
	Column capacity	56 / 42 columns		60 / 45 columns	40 columns	
	Character size	0.99 x 2.4mm (W x H){0.039 x 0.09	,	1.56 x 3.1mm (W x H){0.061 x 0.122"}	1.1 x 2.42mm (W x H)	
		1.41 x 3.39mm (W x H){0.056 x 0.1	•	1.24 x 3.1mm (W x H){0.049 x 0.122"}	{0.043 x 0.099"}	
	Character set	95 Alphanumeric, 37 In	ternation	al, 128 x 8 Graphic, Japanese or Taiwanese Kanji (factory option)		
Printer						
	Print speed	200mm/sec				
		(63 lps, 3.18mm {1/8"} conversion)	)	Approx. 5.7 lps		
		Two-color mode: 78mm/sec	,	(40 columns, 17.8 cpi)	Approx. 1.9 lps	
	Data buffan	(24.5 lps, 3.18mm {1/8"} conversio		and KD (van to 204 KD for example files)		
	Data buffer 45 bytes or 4 KB (up to 384 KB for graphic files)					
	Interfaces	RS-232C / Bi	-direction	nal parallel / RS-485 / USB / IBM® P7 / Con	nect-It*	
	Paper dimensions	79.5 ± 0.5 x diameter 83.0mm		70 to 148 x 150 to 210mm (W x L)		
		{3.13 ± 0.02 x diameter 3.27"}		{2.76 to 5.82 x 5.91 to 8.27"}		
	Paper thickness	0.06 to 0.09mm {0.0024 to 0.0035	"}	0.09 to 0.31mm {0.0035 to 0.012"}	0.09 to 0.2mm {0.0035 to 0.0079"}	
	Copy capacity	_		One original and three copies	One original single-ply	
	Inked ribbon	_		ERC-32B (Black)	ERC-41B (Black)	
	Ribbon life	_		4,000,000 characters	800,000 characters	
	Supply voltage	2	24 VDC ±	10%		
	Current consumption	n A	approx. 1.	.8 A (mean)		
	D.K.D. function	2	2 drivers			
	Reliability MTBF	360,000 hours		180,000 hours		
	MCBF	72,000,000 lines		29,000,000 lines		
	Overall dimensions	1	.86 x 298	x 185mm (W x D x H) {7.3 x 11.7 x 7.3"}		
	Mass			Approx. 5.3 kg (11.7 lbs)		
	Factory options	N	ЛICR devi	ce, endorsement printer, validation		
	Environmental stand	ards		WEEE, RoHS compliant		

#### **Control Board**

EMI standards VCCI class A, FCC class A, CE marking, AS/NZS 3548 Class B

Safety standards UL, CSA, TÜV (EN60950)

cpi: characters per 25.4mm (characters per inch)

lps: lines per second

1 Endorsement printer not available on validation-enabled versions

Epson America, Inc. • 3840 Kilroy Airport Way • Long Beach, CA 90806 • (562) 290-5304 • http://pos.epson.com/financial ©2009 Epson America, Inc. Epson is a registered trademark and Epson Exceed Your Vision is a registered logomark of Seiko Epson Corporation. CaptureOne is a trademark of Epson America, Inc. All other trademarks are the property of their respective owners. Specifications are subject to change without notice.

SD-DSCAPONEE

For more Information contact us at 1-800-666-2980, or visit our website at www.unilinkinc.com

<sup>\*</sup>To find out more about our line of Connect-It interfaces, talk to your UniLink Sales Representative.