

Vision neXt Hardware Options

Inset USB Hub

Plugs into the rear side of the scanner with no footprint increase.
 3 USB ports – 1 exposed and 2 internal.
 Pass-through channel for power cable.

IR Capture

Infrared front image capture for security applications.

3-track Magnetic Card/EMV Smart Card Reader

(future option)

Contact us today at **+1 937.291.2195** or **sales@panini.com** to learn more about how Vision neXt can help reduce transaction processing time and errors, and increase operational savings.

www.panini.com



Receipt Printer

| | |
|-----------------------|--|
| Dimensions | Height 127 mm (5"). Width 137 mm (5.39"). Length: 151 mm (5.94"). |
| Weight | 0.8 Kg (1.8lbs). |
| Print Method | Thermal line printing; monochrome. |
| Speed | 100 mm/sec; ~30lps. |
| Resolution | 203 DPI. |
| Cutter | Automatic, guillotine type, full or partial cut. |
| Paper Roll | 80 mm (width) x 60 mm (diameter). |
| Print Width | 72 mm. |
| Interface | USB 2.0 Hi-Speed. |
| Software | Microsoft Windows driver for XP, Vista, and Windows 7 & 8. OPOS driver (UPOS 1.13 compliant). |
| Certifications | UL / FCC Class A / CE. Electronics and mechanics following European RoHS and WEEE Directives. |
| Power Supply | Desktop Switching Supplier. Autosensing Input from 100 to 240 Vac, 50 to 60 Hz. Output: 24Vdc, 2.7A (65W). Meets CEC level V. |

VNEXT HARDWARE TECH SPECS V6.3 E.1213

Specification subject to change without previous notice.
 This material may not be reproduced without the express written consent of PANINI S.p.A.

For More Information, or to Order:

www.UniLinkinc.com

800.666.2980

Sales@UniLinkinc.com