



To order or for more information:

Tel: 1-800-666-2980

E-mail: Sales@unilinkinc.com

Web: www.unilinkinc.com

Zebra G-Series

Meet the G Series!

Providing ease of use and durability, the G-Series GK and GX models are reliable desktop printing solutions that are always a perfect fit.

You'll feel like they're designed just for you because they offer such a broad array of options. And with both EPL and ZPL pre-installed, you can even switch between languages depending on desired label format.

Basic GK Model: Your Best Value

The Zebra GK model is your best value in a basic desktop thermal printer. Its enhanced performance delivers fast print speeds of up to 5 inches per second and fast first label out. USB and serial connectivity interfaces come standard, or use the ZebraNet® 10/100 Print Server option for distributed printing.

Best-in-Class GX Model: Feature-Rich

The Zebra GX model is best in class with the widest range of features in a desktop thermal printer. It delivers even faster first-label-out and, at 6 inches per second, offers the fastest desktop printer speed on the market. More connectivity choices—USB/serial/parallel, 10/100 Ethernet, and wireless—ensure easy system integration. An LCD panel, included with wireless options, displays prompts and wireless status.

And with options that increase your media flexibility, such as a movable sensor, a peeler, and cutter for labels or receipts—plus a version with 300-dpi resolution—the GX model fits a variety of applications and environments.

GK420D™



Well-suited to retail, healthcare and manufacturing industries, the extra compact GK420d direct thermal printer is the perfect fit wherever you need a low-priced, space-saving printer for receipts, coupons, labels or tags. Along with fast print speeds of up to 5 inches per second, it offers USB/serial connectivity and a 10/100 Ethernet option.

Print Speed

Maximum print speed 5"/127 mm per second

Resolution

203 dpi/8 dots per mm

Memory

8 MB SDRAM
4 MB Flash

Connectivity

Serial RS-232
USB V1.1
ZebraNet 10/100 Ethernet (optional)

Programming Languages

EPL and ZPL co-resident

Maximum Print Area

Width: 4.09"/104 mm
Length: 39"/991 mm

Media Specifications

Label and liner width: 0.75"/19 mm to 4.25"/108 mm

GK420T™



With the GK420t direct thermal/thermal transfer printer, use Zebra's easy ribbon-loading thermal transfer technology to produce crisp, long-lasting label images, or direct thermal technology to print receipts and labels for indoor, short-term use. The GK420t is well-suited to any industry, and provides the same print speeds and connectivity options as the GK420d.

Print Speed

Maximum print speed 5"/127 mm per second

Resolution

203 dpi/8 dots per mm

Memory

8 MB SDRAM
4 MB Flash

Connectivity

Serial RS-232
USB V1.1
ZebraNet 10/100 Ethernet (optional)

Programming Languages

EPL and ZPL co-resident

Maximum Print Area

Width: 4.09"/104 mm
Length: 39"/991 mm

Media Specifications

Label and liner width: 0.75"/19 mm to 4.25"/108 mm
Ribbon width: 1.33"/33.8 mm to 4.3"/109.2 mm
Ribbon length: 244'/74 m



To order or for more information:

Tel: 1-800-666-2980

E-mail: Sales@unilinkinc.com

Web: www.unilinkinc.com

GX420D™



The direct thermal GX420d is extra compact to fit in congested workspaces and produces 203-dpi print resolution at speeds up to 6 inches per second. Its wide range of options include 802.11b/g or Bluetooth® wireless connectivity and 10/100 Ethernet, in addition to standard USB/serial/parallel. Increase your media choices and application flexibility with cutter, peeler, and adjustable black line sensor options.

Print Speed

Maximum print speed 6"/152 mm per second

Resolution

203 dpi/8 dots per mm

Memory

8 MB SDRAM
4 MB Flash
64 MB (68 MB total) Flash with RTC (optional)

Connectivity

Serial RS-232
USB V1.1
Parallel
ZebraNet 10/100 Ethernet (optional)
802.11b/g wireless (optional)
Bluetooth wireless (optional)
Wireless options include LCD for visual communication

Programming Languages

EPL and ZPL co-resident

Maximum Print Area

Width: 4.09"/104 mm
Length: 39"/991 mm

Media Specifications

Label and liner width: 0.75"/19 mm to 4.25"/108 mm

GX420T™



The direct thermal/thermal transfer GX420t has the easiest ribbon-loading system around. Like the GX420d, it produces 203-dpi print resolution at speeds up to 6 inches per second, and like all GX models, it's well-suited to a variety of applications and industries thanks to a wide choice of options.

Print Speed

Maximum print speed 6"/152 mm per second

Resolution

203 dpi/8 dots per mm

Memory

8 MB SDRAM
4 MB Flash
64 MB (68 MB total) Flash with RTC (optional)

Connectivity

Serial RS-232
USB V1.1
Parallel
ZebraNet 10/100 Ethernet (optional)
802.11b/g wireless (optional)
Bluetooth wireless (optional)
Wireless options include LCD for visual communication

Programming Languages

EPL and ZPL co-resident

Maximum Print Area

Width: 4.09"/104 mm
Length: 39"/991 mm

Media Specifications

Label and liner width: 0.75"/19 mm to 4.25"/108 mm
Ribbon width: 1.33"/33.8 mm to 4.3"/109.2 mm
Ribbon length: 244'/74 m

GX430T™



This direct thermal/thermal transfer desktop printer includes a 300-dpi printhead to ensure high-quality, crisp, clear printing of 2-D bar codes, fine text and complex graphics—ideal for high-density data on small labels. Like the GX420t, it has the widest range of features and the easiest ribbon-loading system of any desktop printer on the market. It prints up to 4 inches per second.

Print Speed

Maximum print speed 4"/102 mm per second

Resolution

300 dpi/12 dots per mm

Memory

8 MB SDRAM
4 MB Flash
64 MB (68 MB total) Flash with RTC (optional)Serial

Connectivity

Serial RS-232
USB V1.1
Parallel
ZebraNet 10/100 Ethernet (optional)
802.11b/g wireless (optional)
Bluetooth wireless (optional)
Wireless options include LCD for visual communication

Programming Languages

EPL and ZPL co-resident

Maximum Print Area

Width: 4.09"/104 mm
Length: 39"/991 mm

Media Specifications

Label and liner width: 0.75"/19 mm to 4.25"/108 mm
Ribbon width: 1.33"/33.8 mm to 4.3"/109.2 mm
Ribbon length: 244'/74 m



To order or for more information:

Tel: 1-800-666-2980

E-mail: Sales@unilinkinc.com

Web: www.unilinkinc.com

Specifications at a Glance*

Standard Features

- Print methods: Thermal transfer or direct thermal
- Programming language: EPL and ZPL are standard construction: Dual-wall frame
- Tool-less printhead and platen replacement
- OpenACCESS™ for easy media loading
- Quick and easy ribbon loading
- Auto-calibration of media

Printer Specifications

Resolution

- 203 dpi/8dots per mm;
- 300 dpi/12 dots per mm (GX430t model)

Memory

- Standard: 4 MB Flash; 8 MB SDRAM
- Optional: 8 MB (12 MB total) Flash with RTC (GX models)

Print width

4.09"/104 mm

Maximum Print length

39.0"/990 mm

Maximum Print speed

- GK420: 5"/127 mm per second
- GX420: 6"/152 mm per second
- GX430: 4"/102 mm per second

Media sensors

- Standard: Fixed reflective and transmissive sensors
- Optional: Adjustable reflective black line sensor (GX models)

Media Characteristics

Maximum label and liner length

Maximum non-continuous: 39"/991 mm

Maximum label and liner width

0.75"/19 mm to 4.25"/108 mm

Maximum media roll size

5"/127 mm O.D.

Media thickness

0.003"/0.08 mm to 0.0075"/0.19 mm

Media types

Roll-fed or fan-fed, die-cut or continuous direct thermal labels with or without black line, tag stock, continuous receipt paper, wristbands

Ribbon Characteristics

Outside diameter

1.36"/35 mm

Standard length

244"/74 m

Ratio

1:1 media to roll to ribbon

Width

1.33"/33.8 mm to 43"/109.2 mm

Core inner diameter

0.5"/12.7 mm

Operating Characteristics

Environmental

- Operating temperature: 40° F/4.4° C to 105° F/41° C
- Storage temperature: -40° F/-40° C to 140° F/60° C
- Operating humidity: 5% to 95% non-condensing
- Storage humidity: 5% to 95% non-condensing

Electrical

Auto-detectable (PFC Compliant) 100-240VAV, 50-60Hz

Agency Approvals

- Emissions: FCC Part 15, Subpart B, VCCI, C-Tick
- Emissions and Susceptibility: (CE): EN55022 Class-B, EN61000-3-2, EN61000-3-0 and EN55024, CCC
- Safety: CB Scheme IEC IEC 60950:1991 +A1 +A2 +A3 +A3 +A4, TUV NRTL, IRAM NOM, AAMI, CCC

Physical Characteristics

| | Direct Thermal | Thermal Transfer |
|---------|----------------|------------------|
| Width: | 6.75"/171 mm | 7.6"/193 mm |
| Height: | 6.0"/152 mm | 7.5"/191 mm |
| Depth: | 8.25"/210 mm | 10.0"/254 mm |
| Weight: | 3 lbs/1.4 kg | 4.6 lbs/2.1 kg |

ZebraLink™ Solutions

Software

- ZebraDesigner™ Pro
- ZebraDesigner
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v7.0
- Zebra Universal Driver
- ZebraDesigner Driver

Networking/Connectivity

- ZebraNet® 10/100 Print Server (optional)
- 802.11b/g wireless (optional on GX model)
- Bluetooth wireless (optional on GX model)
- Wireless options include LCD for visual communication

Firmware

- EPL2™
- EPL™ Line Mode (direct thermal only)
- ZPL II®
- Web View
- Alert

Communication and Interface Capabilities

- GX models triple interface standard
- RS-232 serial interface, DB-9
- USB V1.1, bi-directional
- Parallel DB-25 female connector
- ZebraNet 10/100 Print Server (optional)—replaces parallel
- 802.11b/g wireless (optional)—replaces parallel
- Bluetooth wireless (optional)—replaces parallel
- Wireless options include LCD for visual communication

- GK models dual interface standard RS-232 serial interface, DB-9
- USB V1.1, bi-directional
- ZebraNet 10/100 Print Server (optional)—replaces serial

Fonts/Graphics/Symbologies

Fonts and Character Sets

- 16 resident expandable ZPL II bitmap fonts
- One resident scaleable ZPL font
- Five resident expandable EPL2 fonts
- Native open type font support
- Unicode™ compliant for multi-language, on-demand thermal printing

Graphic Features

- Supports user-defined fonts and graphics—including custom logos
- ZPL II drawing commands—for boxes and lines

Bar Code Symbologies

- Bar Code Ratios: 2:1 (non-rotated) and 3:1
- Linear Bar Codes: Codabar, Code 11 (ZPL), Code 128, Code 39, Code 93, Code 93, EAN-13, EAN-8, EAN-14 (ZPL), German Post Code (EPL), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, Japanese Postnet (EPL), ISBT-128 (ZPL), Logmars (ZPL), MSI, Plessey, Postnet, GS1 DataBar (RSS-14), Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC and EAN 2 or 5 digit extensions (ZPL), UPC-A, UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E, and GS1 Databar (formerly RSS)
- 2-Dimensional: Codablock (ZPL), Code 49 (ZPL), Data Matrix, MaxiCode, QR Code, PDF417, MicroPDF417, Aztec (For EPL and ZPL except where noted)

Options and Accessories

- Dispenser—label peel and present with label present sensor
- ZebraNet 10/100 Print Server—Internal Ethernet for network communication and printing
- 802.11b/g wireless (optional)
- Bluetooth wireless (optional)
- Wireless options include LCD for visual communication
- Adjustable media sensor for black line media—GX models only
- Cutter for various media types—GX models only
- 64 MB Flash memory with real-time clock (for total of 68 MB)—GX models only
- Font Packs—Asian and other international font kits
- KDU Plus™ and KDU™ keyboard display units for stand-alone printing solutions

*Specifications subject to change without notice.

©2010 ZIH Corp. EPL, EPL2, OpenACCESS, ZebraLink and all product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic, ZPL, ZPL II, and ZebraNet are registered trademarks of ZIH Corp. All rights reserved. Bluetooth is a registered trademark of Bluetooth SIG, Inc. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners.