



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

fi-6140/fi-6240

Color Duplex Workgroup Scanners



The Fujitsu fi-6140 and fi-6240 scanners bring high performance and advanced features in a compact design

In addition to the fi-6140 scanner being the smallest scanner in its class, both models are able to scan an impressive 60 pages or 120 images per-minute in Monochrome or Grayscale (Letter @ 200dpi) as well as 40 pages or 80 images per-minute in Color (Letter @ 300dpi). Furthermore, the Fujitsu fi-6140 and fi-6240 models are the first scanners in their class to adopt high-end "fi series" functions such as:

- Paper Protection technology: Protects valuable documents by halting the scanning process when it recognizes that a jam is about to occur.
- Intelligent MultiFeed Function (iMFF): Simplifies pre-scanning preparation and improves efficiency by ignoring documents that trigger false multi-feed alerts such as a photo or sticky note.
- Intelligent Capture Correction Function (iCCF): Auto-color recognition, auto-size detection, and auto de-skew correction provides dramatic efficiency by combining fast scanning with simultaneous high speed image processing. Along with ultrasonic double-feed detection, long document scanning (up to 10 feet), dual interfaces (ultra SCSI and USB 2.0), and embossed card scanning, these scanners can continuously feed up to 3 hard cards (up to 1.4 mm thick) through the Auto Document Feeder (ADF).

FUJITSU THE POSSIBILITIES ARE INFINITE

The fastest and most advanced scanners in their class*.

- Fast, 60 ppm/120 ipm scanning in monochrome and grayscale
- Best in class 300 dpi color scanning at 40 ppm/80 ipm
- First scanners in their class to offer Intelligent MultiFeed Function (iMFF) as well as advanced Paper Protection technology
- Robust 50-page Automatic Document Feeder (ADF) with enhanced hard and embossed card scanning (Example: credit or healthcare cards)
- Comes with Kofax® VRS® Professional, Adobe® Acrobat® 8 Standard, and ScandAll Pro
- One-year Limited Warranty with

Fully Loaded One Box Solution.

The Fujitsu fi-6140 and fi-6240 scanners conveniently include everything in the box to get organizations up and scanning. With the full version of Kofax VRS® Professional, Adobe® Acrobat® Standard, and ScandAll Pro software, users get image enhancement functionality as well as the option of scanning directly to PDF, file, print or batch. And the one-year Limited Warranty, along with eligibility for the Fujitsu Advance Exchange Program, provides peace-of-mind. For full details on the Limited Warranty and on all Fujitsu service programs, go to www.ImageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc. is a subsidiary of Fujitsu Limited, a leading provider of customer-focused IT and communications solutions for the global marketplace. FCPA provides innovative solutions for the U.S. marketplace. Current product and service offerings include high performance hard disk drives, Magneto-Optical drives, scanners and scanner maintenance, palm vein recognition technology, 10Gb Ethernet switches and degaussers.



To order or for more information:

Tel: 1-800-666-2980

E-mail: info@unilinkinc.com

Web: www.unilinkinc.com

fi-6140/fi-6240

Color Duplex Workgroup Scanners

Functional Specifications

Image Sensor Type	
fi-6140	Color Charge Coupled Device (CCD) x 2
fi-6240	Color Charge Coupled Device (CCD) x 3
Light Source	White cold cathode discharge lamp
Optical Resolution	600 dpi
Output Resolution ¹	
Color (24 bit)	50 to 600 dpi
Grayscale (8 bit)	(adjustable by 1 dpi increments, 1200 dpi) ²
Monochrome	
Output Format	
Color:	24 bit, 8 bit/4 bit;
Grayscale:	8 bit, 4 bit;
Monochrome:	1 bit
AD Converter	1024 levels (10 bit)

Scanning speeds

Output	(Letter/A4 size) ³	Simplex	Duplex
Color ⁴	200 dpi	40 ppm	80 ipm
	300 dpi	40 ppm	80 ipm
Grayscale ⁴ /	200 dpi	60 ppm	120 ipm
Monochrome	300 dpi	40 ppm	80 ipm
ADF Capacity ⁵	50 Sheets (letter/A4, 20 lb.)		
Document size	ADF minimum	2 in. x 3 in.	
	ADF maximum	8.5 in. x 14 in.	
	Flatbed (fi-6234 only)	8.5 in x 11.69 in.	
ADF Feeding	Normal	11 to 56.2 lb. (41 to 210g/m ²)	
Paper Weight	A8 sheets	34 to 56.2 lb. (127 to 210g/m ²)	
(Thickness)	Card ⁶ (1.4 mm) ⁷	Portrait and Landscape feedings ⁸	
Interface	Ultra SCSI (50m) / High Speed USB 2.0		

Physical Specifications

Power requirements	100 – 240 VAC, 50/60 Hz
Power	fi-6140 42W or less (Sleep: less than 6.2W)
Consumption	fi-6240 28 – 34 W, Energy saving mode: 12 W
Environmental Compatibility	ENERGY STAR® and RoHS
Operating	Temperature 42° to 95°F (5° to 35°C)
Environment	Relative humidity 20% – 80%(non- condensing)
Dimensions	fi-6140 11.8 x 6.4 x 6.2 in. (301 x 160 x 158 mm)
(WxDxH) ¹⁰	fi-6240 11.8 x 22.9 x 9.0 in. (301 x 567 x 229 mm)
Weight	fi-6130 9.24 lb. (4.2 kg)
	fi-6230 19.36 lb. (8.8 kg)

Limited Warranty	One-year. Advance Exchange program also available; restrictions apply.
Service Options Post-Warranty:	Advance Exchange Plus; restrictions apply.
Inbox Contents	TWAIN, ISIS™, USB cable, AC adapter
Bundled Software	Adobe® Acrobat® Standard, Kofax® VRS® Professional and ScandAll Pro
Options	Software IPC, Imprinter, (Flatbed Cover Black Background for fi-6240)
OS Support	Microsoft® Windows® 2000 Professional / Microsoft® XP (32 bit/64 bit) /Microsoft® Windows Server™ Windows Vista™ (32 bit/64 bit)
Features	Ultrasonic Double Feed Detection, Intelligent Multi-Feed Function (iMFF), Paper Protection Function, Embossed Card Scanning Capability, Long Document Scanning, Automatic Color Recognition, Automatic Paper-Size Detection, Automatic De-skew Correction,
Part Number	fi-6140 PA03540-B005
	fi-6230 PA03540-B505

1 Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.

2 Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher).

3 Actual scanning speeds are affected by data transmission and software processing times.

4 JPEG compressed figures.

5 Maximum capacity varies, depending upon paper weight.

6 Supports ISO7810 embossed cards

7 Able to digitize cards that are up to 1.25mm thick when scanning in monochrome at 200dpi (60ppm).

8 Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feeding.)

9 Ultra SCSI interface cannot be used simultaneously with USB2.0.

10 Excluding the ADF paper chute and stacker

©2007 Fujitsu Computer Products of America, Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks and The Possibilities are Infinite is a trademark of Fujitsu Limited. Adobe and Acrobat are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries. Microsoft, Windows and Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. ISIS is a registered trademark of Pixel Translations, a division of Captiva Software Corporation. VRS is a registered trademark of Kofax Image Products, Inc. As an ENERGY STAR® Partner, Fujitsu Ltd. has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a U.S. registered trademark. All other trademarks are the property of their respective owners. All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Computer Products of America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price and warranty, post-warranty and service programs.

Fujitsu Computer Products of America, Inc.

<http://us.fujitsu.com/fcpa>

1255 East Arques Avenue Sunnyvale, CA 94085-4701. (800) 626-4686 (408) 746-7000 info@fcpa.fujitsu.com