


# MAXIMUM PERFORMANCE. MINIMUM SPACE.

www.UniLinkinc.com 800.666.2980

UniLink

Sales@UniLinkinc.com





## SOPHISTICATED, FLEXIBLE, SECURE

- · High-speed graphics processor and generous memory bring customer messaging and video advertising campaigns to life
- Crystal clear, 4.3" flush mount display
- Clean lines and modern, sleek design make a powerful statement in the lane or on a countertop
- · State-of-the-art stylus for a clean and sleek look
- · Chemically-hardened screen, built for the long haul
- · Linux-based OS and application development environment offer maximum flexibility
- NFC/Contactless support to quickly capture new markets as they
- · Large screen area efficiently accommodates optional signature capture along with scrolling account activity, branding and promotional offers
- Integrated, tactile, backlit keypad to speed customers through lanes while reducing errors
- Remotely inject encryption keys anytime, anywhere with VeriShield Remote Key option added

## THE TOTAL PACKAGE IN A SMALLER FORM

- Ideal platform for a variety of value-added services, such as administrating loyalty schemes, gift card issuance and top-up services
- VeriFone HQ software simplifies device management and reduces overall support costs, all while easily integrating into your current environment. It offers device management, diagnostics and content management capabilities
- Web Development Environment (WDE) provides a unique combination of web technology and a secure payment framework for powerful and flexible application development platforms
- · Supports end-to-end security with VeriShield Total Protect, secured by RSA, which eliminates sensitive cardholder data from the payment device and merchant infrastructure through tokenization
- Compatible with legacy or existing MX 800 series product solutions



### Processor

400 MHz 32 bit ARM 11

128 MB SDRAM + 256 Flash Flash is field upgradable via USB or SD

### Connectivity

Connect I/O: Ethernet 10/100BaseT, USB host/device. Serial Interfaces RS-232, RS 485; IBM Tailgate; WiFi; Compatible with existing MX 800 Series; Cabling solutions

## Display

4.3" (480 x 272) 65,536 Color, GFX Wide Screen Capacitive/chemically-hardened glass

Single speaker

Line out port available to drive externally powered speakers

## Security/Encryption

PCI PTS 3.0, EMV Level 1 and 2, Triple DES, Master Session, DUKPT, Interac, AES

## **Smart Card Reader**

Landed Reader, Up to 3 SAMs, software controllable prompts

### Magnetic Card Reader

Triple Track bi-directional Software-controllable LED prompt

Form Agent, IBM EFT, NCR EFT, Secure browser Web Development Environment (WDE)

## **Operating System**

Embedded Linux with VeriFone security enhancements

### NFC/Contactless

ISO 14443 AB Certified MSD/EMV Completely enabled

Recessed for privacy 13 laser-etched tactile keys Backlit keypad

Non-mechanical Field replaceable

## **Graphical Processor**

Built-in graphical processor